

2008 Product Catalog

Outdoor Optics

BETTER OPTICS, GREATER VISION



Dear Weaver® Hunter and Shooter,

Thank you for reviewing the new Weaver 2008 product catalog.

Weaver has long set the standard for precision and reliability in the shooting sports, earning it a loyal following at the firing lines of major matches across America.

Shooters know and trust Weaver's performance and technology. In fact, Weaver is renowned for its long history of innovation – starting in 1930, when Bill Weaver introduced his first scope.

This spirit of innovation remains an ongoing part of the Weaver tradition. Over the years, Weaver has developed the first scope with internal adjustments, O-ring sealing and QuadZero™, the windage and elevation adjustment system that uses double in-line force to hold zero unerringly, shot after shot after shot.

Innovations like these have consistently convinced hard-core shooters to prefer Weaver scopes over all others.

Going back to my years growing up in Minnesota, I still have fond memories of taking my first shot at a squirrel with my old Remington® single-shot .22. Even then, I appreciated the value of a sound rifle and a clear, accurate scope.

Today, I recognize and value the competitive advantages Weaver continues to provide. As such, I am proud of our products and can recommend every one with confidence and conviction.

So please join us in this review of our latest offerings. And once again discover why Weaver has remained America's scope of choice for over 75 years.

Steve Muellner
President and CEO
Weaver Optics



Weaver QuadZero™ Adjustment System –

A Commitment To Innovation

Double the Springs | Double the Force | Double the Control | Double the Precision


Weaver's patented QuadZero four-point windage and elevation adjustment system is one of the most reliable and accurate in the world.

Unlike most riflescopes which use one leaf spring and the windage and elevation dials to make adjustments – Weaver's QuadZero uses two compression springs and the windage and elevation dials.

With the common one-spring system, adjusting one screw too far can cause the spring to affect the adjustment of the other screw.

With QuadZero, its two springs are aligned directly across from the windage and elevation adjustments, so each adjustment can be made independently for pinpoint accuracy.

The increased force bearing down from the second spring also helps hold zero 60% better than most premium scopes. Click adjustments remain consistent to a quarter minute of angle, and zero is maintained in a vise-like grip to 10,000 rounds from a .375 H&H magnum rifle – providing you with a reliability, repeatability and durability that is unrivaled in this class.





The Grand Slam[®]


Optical Superiority



See page 15
LIMITED
LIFETIME
WEAVER
WARRANTY
for additional information



6-20 x 40 A/O
800476



**NEW
FOR
2008**



10x40 Tactical
801040T

**NEW
FOR
2008**



4.5-14x40 Tactical
800475T



1.5-5 x 32
800471



3.5-10 x 50
800589




4.5-14 x 40 A/O
800475



3.5-10 x 40
800474

ELEVATION ADJUSTMENT
FORCE



Built To Be the Best

Weaver's award-winning Grand Slam is consistently rated as one of the best all-round scopes anywhere.

Featuring Weaver's QuadZero™ rock-solid, independent windage and elevation adjustment system, the Grand Slam delivers unrivalled reliability and superior performance in every department.

Fully multi-coated Japanese optics yield 94% light transmission at 550nm, with edge-to-edge clarity, reduced glare and incredible image brightness – all combining to make the Grand Slam the perfect variable power scope for all low light conditions.

The Grand Slam's fast-focus eyepiece adjustment, SureGrip™ power change ring and adjustable objective make it quick and easy to adjust the scope – even when wearing wet, heavy gloves.

The one-piece, aircraft-grade aluminum tube construction is waterproof, fogproof and shockproof to 10,000 rounds from a .375 H&H magnum rifle.

MODEL	DESCRIPTION POWER, OBJECTIVE	SPECIAL FEATURES	FINISH	RETICLE	EXIT PUPIL (MM)	FIELD OF VIEW FT @ 100 YDS/M @ 100M	EYE RELIEF (IN./MM)	LENGTH (IN./MM)	CLICK VALUE IN. @ 100 YDS/M @ 100M	ADJUSTMENT RANGE IN. @ 100 YDS/M @ 100M	WEIGHT (OZ./G)
800471	1.5-5 x 32		Matte	Dual-X	17.4-6.2	71-21/23.6-7.0	3.3/84	10.3/262	1/4 / 7	120/3.3	11.5/326
800473	3-10 x 40		Matte	Dual-X	12.6-4	35-11.3/11.7-3.8	3.5/89	11.9/302	1/4 / 7	70/1.9	13/369
800588	3-10 x 40		Silver	Dual-X	12.6-4	35-11.3/11.7-3.8	3.5/89	11.9/302	1/4 / 7	70/1.9	13/369
800474	3.5-10 x 50		Matte	Dual-X	11.5-4.5	23.6-10.9/7.9-3.6	3.5/89	12.8/325	1/4 / 7	65/1.8	16.3/462
800589	3.5-10 x 50		Silver	Dual-X	11.5-4.5	23.6-10.9/7.9-3.6	3.5/89	12.8/325	1/4 / 7	65/1.8	16.3/462
800475	4.5-14 x 40	Adj. Obj.	Matte	Dual-X	8.8-2.6	22.5-10.5/7.5-3.5	3.5/89	14.3/363	1/4 / 7	50/1.4	16.5/468
800475T	4.5-14 x 40	Tac. Tur.	Matte	Mil-Dot	8.8-2.6	22.5-10.5/7.5-3.5	3.5/89	14.3/363	1/4 / 7	50/1.4	16.5/468
800590	4.5-14 x 40	Adj. Obj.	Silver	Dual-X	8.8-2.6	22.5-10.5/7.5-3.5	3.5/89	14.3/363	1/4 / 7	50/1.4	16.5/468
800469	6-20 x 40	Adj. Obj.	Matte	Varminter	6.6-2	16.5-5.3/5.5-1.8	3/76	14.3/363	1/8 / 3.5	40/1.1	17.8/505
800476	6-20 x 40	Adj. Obj.	Matte	F/C Dot	6.6-2	16.5-5.3/5.5-1.8	3/76	14.3/363	1/8 / 3.5	40/1.1	17.8/505
801040T	10x40	Tac. Tur.	Matte	Mil-Dot	4	9.3/3.1	4/102	14/356	1/4 / 7	60/1.7	16.6/471




Classic[®] Extreme

Unconditional Performance In Every Kind Of Condition



2.5-10 x 50 SF
800704



2.5-10 x 56 SF
800706



1.5-4.5 x 24
800702

Extremists Welcomed

Time of day, weather and field conditions don't stand a chance with the Classic Extreme.

¼ MOA, audible push-pull windage and elevation adjustments for pinpoint, precise accuracy.

Delivering 95% light transmission at 550nm through fully multi-coated optics, the Classic Extreme's exceptional optical design makes it the ultimate scope for spotting brown game in low light.

Four inches of eye relief makes aiming from awkward positions easier, even when shooting up or down hill. And the one-piece, fogproof, waterproof and shockproof 30mm tube provides more windage and elevation travel – critical for those tough, extremely long range shots.


Other features include oversized, push/pull resettable windage and elevation dials, fast-focus eyepiece, internally-ruled objective assembly for eliminating stray light, side-parallax adjustments on all 2.5-10 models, and your choice of illuminated 1 MOA Dot Dual-X and illuminated German #4 reticles. It all comes together to give the edge you need to make that once-in-a-lifetime shot even in the worst weather and lowest light.

MODEL	DESCRIPTION POWER, OBJECTIVE	SPECIAL FEATURES	FINISH	RETICLE	EXIT PUPIL (MM)	FIELD OF VIEW FT @ 100 YDS/M @ 100M	EYE RELIEF (IN./MM)	LENGTH (IN./MM)	CLICK VALUE IN. @ 100 YDS/M @ 100M	ADJUSTMENT RANGE IN. @ 100 YDS/M @ 100M	WEIGHT (OZ./G)
800701	1.5-4.5 x 24		Matte	ill. German #4	16-5.3	65.6-22.2/21.8-7.4	4/102	9.7/246	1/4 / 7	50/1.4	15.6/442
800702	1.5-4.5 x 24		Matte	ill. Dual-X	16-5.3	65.6-22.2/21.8-7.4	4/102	9.7 9.7/246	1/4 / 7	50/1.4	15.6/442
800703	2.5-10 x 50	Side Focus	Matte	ill. German #4	20-5.2	36.7-10.1/12.2-3.4	4/102	12.9/328	1/4 / 7	50/1.4	24/680
800704	2.5-10 x 50	Side Focus	Matte	ill. Dual-X	20-5.2	36.7-10.1/12.2-3.4	4/102	12.9/328	1/4 / 7	50/1.4	24/680
800705	2.5-10 x 56	Side Focus	Matte	ill. German #4	22.4-5.6	36.7-10.1/12.2-3.4	4/102	13.8/351	1/4 / 7	50/1.4	26/737
800706	2.5-10 x 56	Side Focus	Matte	ill. Dual-X	22.4-5.6	36.7-10.1/12.2-3.4	4/102	13.8/351	1/4 / 7	50/1.4	26/737



Classic V-Series™

Master Every Variable




6-24 x 42 A/O
849411



3-9 x 38
849402



2-10 x 38
849405



Variability. Reliability. Dependability.

Hunt from forest and brush to wide open spaces – from early morning to late dusk – and conquer every condition with the variable-power Classic V-Series scopes from Weaver.

Fully multi-coated high-quality Japanese optics give you the brightness (94% light transmission) and edge-to-edge clarity needed for maximizing those premium twilight hunting hours.

Built to provide a large field of view, generous eye relief, and quick-change power adjustments, all Classic V-Series scopes deliver the versatility needed to locate and hone in on even the hardest to spot game.

The solid, one-piece, aircraft-quality aluminum body produces a waterproof, fogproof, and shockproof riflescope that ensures years of rugged reliability.

MODEL	DESCRIPTION POWER, OBJECTIVE	SPECIAL FEATURES	FINISH	RETICLE	EXIT PUPIL (MM)	FIELD OF VIEW FT @ 100 YDS/M @ 100M	EYE RELIEF (IN./MM)	LENGTH (IN./MM)	CLICK VALUE IN. @ 100 YDS/M @ 100M	ADJUSTMENT RANGE IN. @ 100 YDS/M @ 100M	WEIGHT (OZ./G)
849400	1-3 x 20		Matte	Dual-X	15-6.6	87-30.8/29-102	3.1-3.1/79-79	9.1/231	1/4 / 7	120/3.3	8.5/241
849399	2-7 x 32		Matte	Dual-X	15-4.6	45-15/15-5.0	4.5-3.5/114-89	10.9/277	1/4 / 7	70/1.9	10/284
849402	3-9 x 38		Matte	Dual-X	12.7-4.2	34-11.4/11.3-3.8	3.3-3/84-76	12.3/312	1/4 / 7	70/1.9	11.3/320
849406	2-10 x 38		Silver	Dual-X	19-3.8	38-9.6/12.5-3.2	3.3-3/84-76	12.5/317	1/4 / 7	70/1.9	11/312
849405	2-10 x 38		Matte	Dual-X	19-3.8	38-9.6/12.5-3.2	3.3-3/84-76	12.5/317	1/4 / 7	70/1.9	11/312
849410	4-16 x 42	STT*	Matte	F/C Dot	10.5-2.6	24.4-7.0/8.1-2.3	3.1-3/79-76	14/356	1/4 / 7	50/1.4	16.8/476
849409	4-16 x 42	STT*	Matte	F/C	10.5-2.6	24.4-7.0/8.1-2.3	3.1-3/79-76	14/356	1/4 / 7	50/1.4	16.8/476
849408	4-16 x 42	STT*	Matte	Dual-X	10.5-2.6	24.4-7.0/8.1-2.3	3.1-3/79-76	14/356	1/4 / 7	50/1.4	16.8/476
849412	6-24 x 42	STT*	Matte	Mil Dot	7-1.2	15.7-4.4/5.2-1.5	3.1-3.1/79-79	14.1/358	1/8 / 3.5	35/1.0	17.6/499
849411	6-24 x 42	STT*	Matte	Varminter	7-1.2	15.7-4.4/5.2-1.5	3.1-3.1/79-79	14.1/358	1/8 / 3.5	35/1.0	17.6/499

* Semi Target Turret



Classic K-Series™

Fixed Power – Simple. Durable. Accurate.



4x38
849415



Dual-X



Set To Be Simple, Accurate And Durable

Nothing beats long-term durability and ease of use like a Classic K-Series scope.

Crafted from a one-piece aircraft-grade aluminum tube that holds its lenses in perfect permanent alignment, the Classic K-Series fixed power scopes are solidly built to take heavy recoil punishment and hold zero to 10,000 rounds from a .375 H&H magnum rifle.

And because Classic K-Series fixed scopes present a consistent field of view that's perfect for open field hunting, they are among the easiest scopes any instinctive shooter will ever use regardless of the range.

Classic K-Series' fully multi-coated Japanese optics dramatically increase image brightness and contrast while helping eliminate glare.

And as you expect with all Weaver products, Classic K-Series riflescopes are fully waterproof, shockproof and fogproof.


MODEL	DESCRIPTION POWER, OBJECTIVE	SPECIAL FEATURES	FINISH	RETICLE	EXIT PUPIL (MM)	FIELD OF VIEW FT @ 100 YDS/M @ 100M	EYE RELIEF (IN./MM)	LENGTH (IN./MM)	CLICK VALUE (MOA) IN. @ 100 YDS/M @ 100M	ADJUSTMENT RANGE IN. @ 100 YDS/M @ 100M	WEIGHT (OZ./G)
849415	4 x 38		Matte	Dual-X	9.5	23.1/7.7	3.2/8	11.5/292	1/4 / 7	120/3.3	9.9/281
849418	6 x 38		Matte	Dual-X	6.3	18.4/6.2	3.2/8	11.6/295	1/4 / 7	80/2.2	9.8/278

Classic™ Rimfire



2.5-7 x 28
849431

Dual-X



Small Caliber, High Performance

Weaver takes rimfire riflescopes as seriously as its big game brethren. Every Classic Rimfire scope incorporates many of the exact same features found on Weaver's top-of-the-line models.

Designed to bring out the best in rimfire and adult air rifles, the Classic Rimfire comes in variable and fixed power models – with fully multi-coated, non-glare optics that produce edge-sharp, low-light brightness, even in the duskiest of conditions.

All scopes feature rugged, aircraft-grade one-piece aluminum construction. Waterproof, fogproof and shockproof, the Classic Rimfire is designed to withstand the multi-directional recoil from the heaviest spring-loaded adult airguns.

Parallax is set at 50 yards for ideal rimfire target acquisition and accuracy.



MODEL	DESCRIPTION POWER, OBJECTIVE	SPECIAL FEATURES	FINISH	RETICLE	EXIT PUPIL (MM)	FIELD OF VIEW FT @ 100 YDS/M @ 100M	EYE RELIEF (IN./MM)	LENGTH (IN./MM)	CLICK VALUE IN. @ 100 YDS/M @ 100M	ADJUSTMENT RANGE IN. @ 100 YDS/M @ 100M	WEIGHT (OZ./G)
849398	3 - 9 x 32	Adj. Obj.	Matte	Dual-X	10.6-3.5	37-13/12.3-4.3	3.7/94	11.3/287	1/4 / 7	60/1.7	12/340
849430	4 x 28		Matte	Dual-X	7	21.8/7.3	3.3/84	10.3/262	1/4 / 7	80/2.2	8.5/241
849431	2.5 - 7 x 28		Matte	Dual-X	11.2-4	41.3-15.7/13.8-5.2	3.7/94	11.5/292	1/4 / 7	80/2.2	9.75/278
849432	2.5 - 7 x 28		Silver	Dual-X	11.2-4	41.3-15.7/13.8-5.2	3.7/94	11.5/292	1/4 / 7	80/2.2	9.75/278



T-Series™



36 x 40 A/O
849970



Weaver QuadZero™ Adjustment System

Double The Springs. Double The Force.
Double The Control. Double The Precision.

Weaver's patented QuadZero™ four-point windage and elevation adjustment system is one of the most reliable and accurate in the world. It features two springs for independent windage and elevation adjustment, plus a greater vise-like force to maintain zero to 10,000 rounds from a .375 H&H magnum rifle – unrivaled in its class.

The Target and Varmint Terminator

Whether it's putting repeated rounds into the same hole or picking off small varmints at hundreds of yards – Weaver's T-Series fixed riflescopes give you the eighth MOA accuracy you need to be dead on, shot after shot.

Each T-Series scope features the incredibly accurate QuadZero™ adjustment system that gives you more accurate, completely independent windage and elevation control.

An adjustable objective provides parallax-free shooting – so no matter how off-center your eyepiece-to-eye alignment is, your point of impact won't be affected.

Fully multi-coated Japanese optics increase brightness to 94% at 550nm. These superior optics punch up the contrast, eliminate glare and deliver unparalleled clarity.

Every T-Series scope comes with traditional eyepiece focus, a sunshade, screw-in metal lens caps and an extra pair of oversized benchrest adjustment knobs.

MODEL	DESCRIPTION POWER, OBJECTIVE	SPECIAL FEATURES	FINISH	RETICLE	EXIT PUPIL (MM)	FIELD OF VIEW FT @ 100 YDS/M @ 100M	EYE RELIEF (IN./MM)	LENGTH (IN./MM)	CLICK VALUE IN. @ 100 YDS/M @ 100M	ADJUSTMENT RANGE IN. @ 100 YDS/M @ 100M	WEIGHT (OZ./G)
849970	36 x 40	AdjObj/SunShade	Matte	F/C	1.16	3/1	3/76	15.4/391	1/8 / 3.5	60/1.7	17/487
849981	36 x 40	AdjObj/SunShade	Silver	F/C	1.16	3/1	3/76	15.4/391	1/8 / 3.5	60/1.7	17/487
849974	36 x 40	AdjObj/SunShade	Matte	1/8 MOA Dot	1.16	3/1	3/76	15.4/391	1/8 / 3.5	60/1.7	17/487
849969	36 x 40	AdjObj/SunShade	Silver	1/8 MOA Dot	1.16	3/1	3/76	15.4/391	1/8 / 3.5	60/1.7	17/487
849976	24 x 40	AdjObj/SunShade	Gloss	1/8 MOA Dot	1.6	4.4/1.5	3/76	15.4/391	1/8 / 3.5	60/1.7	16/454

Classic™ Handgun



4 x 28
849425

Dual-X



2.5-8 x 28
849429



Magnum Force Reliability, High Impact Accuracy

Handguns demand a scope that is built to withstand the brutal, shot-after-shot pounding from today's most powerful revolvers and single-shot pistols. Designed for the tremendous recoil of 1,000 rounds from a .454 Casull® revolver, Weaver's Classic Handgun scopes deliver the goods on rugged, reliable, repeatable accuracy.

Fully multi-coated Japanese optics increase brightness, eliminate glare and transmit crisp, clear, edge-to-edge images.

Featuring a 50-yard parallax setting, the fixed power Classic scopes provide unlimited eye relief.

MODEL	DESCRIPTION POWER, OBJECTIVE	SPECIAL FEATURES	FINISH	RETICLE	EXIT PUPIL (MM)	FIELD OF VIEW FT @ 100 YDS/M @ 100M	EYE RELIEF (IN./MM)	LENGTH (IN./MM)	CLICK VALUE IN. @ 100 YDS/M @ 100M	ADJUSTMENT RANGE IN. @ 100 YDS/M @ 100M	WEIGHT (OZ./G)
849427	1.5 - 4 x 20		Gloss	Dual-X	13.3-5.5	15.5-6.5/5.5-2.2	14-22/ 356-559	9/229	1/4 / 7	60/1.7	8.2/232
849429	2.5-8 x 28		Matte	Dual-X	11.2-3.5	12.2-3.9/4.1-1.3	16-24/ 406-61	9.4/239	1/4 / 7	70/1.4	9.1/258
849446	2.5-8 x 28		Silver	Dual-X	11.2-3.5	12.2-3.9/4.1-1.3	16-24/ 406-610	9.4/239	1/4 / 7	70/1.4	9.1/258
849424	2 x 28		Silver	Dual-X	16	21/7	14-29 / 356-737	8.4/213	1/4 / 7	120/3.3	6.7/190
849425	4 x 28		Gloss	Dual-X	7	8.3/2.8	12-18 / 305-457	8.5/2.6	1/4 / 7	100/2.8	6.4/181



Grand Slam[®] Binoculars



7 x 42mm
849627

See The World Clearly

Get Weaver Grand Slam quality in a full-size binocular. Grand Slam binoculars incorporate phase-coated BaK-4 (Barium crown glass) roof prisms and fully multi-coated Japanese optics for unsurpassed light transmission and bright, sharp, glare-free images.

Grand Slams are Nitrogen gas-purged for 100% waterproof and fogproof use in the most rugged and wet conditions.

Pop-up eyecups help provide a full field of view, even for eyeglass wearers. Durable rubber armor protects against sudden impact and provides a sure, non-slip grip. Comes with a rugged, high-quality case and strap.

MODEL	DESCRIPTION POWER, OBJECTIVE	OBJECT LENS	FINISH	EXIT PUPIL (MM)	FIELD OF VIEW FT @ 100 YDS/M @ 100M	EYE RELIEF (IN./MM)	OVERALL LENGTH (IN./MM)	WIDTH (IN./MM)	OVERALL HEIGHT (IN./MM)	WEIGHT (OZ./G)	PRISM
849627	7 X 42		Rubber Armor	6	420/140	20/508	5.125/130.2	2.125/54	6.25/158.75	31/878.8	Roof
849628	10 x 42		Rubber Armor	4.2	341/113.6	17/431.8	5.125/130.2	2.125/54	6/152.4	31/878.8	Roof

Weaver Service and Support



Limited Lifetime Warranty: Weaver warrants this product to be free of defects in materials and workmanship for as long as it is owned by the original owner. Weaver will repair or replace any such defective product when it is returned by the original owner. The repair or replacement will be without charge except for reasonable shipping, handling and insurance charges. This is the only expressed warranty that applies to this WEAVER product. TO THE EXTENT ALLOWED BY LAW, ANY IMPLIED WARRANTY OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE APPLICABLE TO THIS PRODUCT IS LIMITED IN DURATION TO THE DURATION OF THIS EXPRESSED WARRANTY. Repair or replacement is the exclusive remedy under this expressed warranty and any applicable implied warranty. This warranty does not cover defects or problems caused by abuse, by improper handling or installation, or by unauthorized repair. Weaver shall not be liable for any consequential or incidental damages including, but not limited to, economic loss or lost profits. Some states do not allow limitations on how long an implied warranty lasts or do not allow the exclusion of consequential or incidental damages, so the above limitation or exclusion may not apply to you. This warranty gives you, the original owner, specific legal rights and you may also have other rights which may vary from state to state.

RGA Number Required: Prior to the return of any product or part, a Return Goods Authorization (RGA) number must be obtained by writing to Weaver's Customer Service Department or by calling 800-285-0689. Each returned part or product must include a written statement detailing the nature of the claimed defect, as well as the owner's name, address, phone number, and a copy of the original sales invoice.

Packaging: If possible, ship the product in its original packaging. Please be sure to wrap the package securely and use filament strapping tape on the outside of the package. Send only the product to be repaired. Please do not send accessory items such as dust caps, carrying case, mounts, etc.

What to Include:

- A short note explaining the reason you are sending the product in for repair.
- Your daytime phone number.
- An address for returning your product to you. (No PO boxes please.)
- A check or money order in the amount of \$10.00 to cover shipping and handling fees. Canadian customers please include a money order in U.S. dollars for \$10.00
- Photocopy of your sales receipt.

Shipping: We recommend that you ship your product to us by a tracked parcel service. We also recommend that you insure the shipment against loss. Many carriers automatically insure packages up to a certain nominal amount, typically \$100. Please check to see if the insurance provided by the carrier is adequate to cover the replacement value of your product. If you live in the United States, your product should be sent, freight prepaid, to:

Weaver Optics
Attention: Repair Department
6001 Oak Canyon
Irvine, Ca 92618

In other countries, please contact your Weaver® International Distributor in your country for service.

Repair Process: After receiving your returned product, a Weaver repair technician will evaluate your product to determine what repairs are needed and whether or not your product is covered by an applicable warranty. If the product is covered by our warranty, you will receive no additional correspondence and we will either repair or replace your product, at our option. Your repaired product, or a comparable replacement of equal value and function, will be shipped back to you. If, however, your product is no longer covered by our warranty, one of our technicians will provide you with an estimate of the cost to repair or replace your product. You will have 20 business days to respond and either accept or decline the recommendation. If you accept the recommendation for repair or replacement you will need to provide the payment requested before we will commence work on your product. Payment can be made in the form of a check, money order, or if you prefer, by MasterCard or VISA. If you do not respond within the 20 business day period, we will return the un-repaired product to you. If the product is covered by a warranty, you will receive no additional correspondence.



Weaver Outdoor Optics
6001 Oak Canyon, Irvine, CA 92618
(800) 285-0689
www.weaveroptics.com
printed in the USA | wc-2008