



H3

2009





The 2009 H3 comes with available front and rear locking differentials. No other vehicle in its class offers these essential off-road tools as factory features.

Welcome to the open.

Countless adventures are well within your grasp while behind the wheel of the ultimately capable 2009 HUMMER H3. The H3 is the most capable off-road vehicle in its class. It has best-in-class approach and departure angles,* a 45.1:1 crawl ratio and full underbody protection with four skid plates.

This year, the H3 stepped up its capabilities even further. Its already celebrated available locking rear differential is now complemented by an available front locking differential, bumping the crawl ratio up to a staggering 68.9:1. When the differentials are locked, wheels get maximum torque allowing the H3 to easily navigate uneven terrain.

Legendary HUMMER power comes standard with a Vortec 3700 in-line 5-cylinder engine, a perfect balance of performance and efficiency. With the H3 Alpha, that engine grows to an impressive 5.3L V8.

As one of the most capable off-road vehicles on the planet, the H3 must offer up ample safety features to help ensure not only protection, but peace of mind.

Features like StabiliTrak Electronic Stability Control System, Hill Start Assist which helps prevent roll-back after stopping on a steep hill, available OnStar® Turn-by-Turn navigation,† and standard head curtain side air bags with roll over sensing system.‡

*All claims based on 2008 GM Mid Lux Utility and Mid Utility Traditional segments. †Requires Directions & Connections plan. Not available in certain areas. Visit onstar.com for details, system limitations, and coverage map. ‡Always use safety belts and the correct child restraints for your child's age and size. Even in vehicles equipped with the Passenger Sensing System, children are safer when properly secured in the rear seat in the appropriate infant, child or booster seat. Never place a rear-facing infant restraint in the front seat of any vehicle equipped with an active frontal air bag. See the vehicle Owner's Manual and child safety seat instructions for more safety information.





VORTEC 3700

239

HORSEPOWER

241 lb-ft

TORQUE @ 4600 RPM

223 cu. in.

DISPLACEMENT

45.1:1

CRAWL RATIO

AVAILABLE LOCKING FRONT AND REAR DIFFERENTIALS



H3

N 40°5.9 W 083°6.3 ▲ H309 ▲ 03 × BM 613

Every HUMMER is designed to take you to remarkable places. Choose the one that is right for you and then make it your own through a variety of trim packages, color, and interior options.



H3



H3 ALPHA



H3^x

Models, trims, colors and more.

H3 The fully off-road capable, midsize HUMMER. Its smaller size makes it more nimble, more fuel efficient,* and easy to drive.

H3 ALPHA The H3 – only more powerful. Featuring more horsepower, more torque, more towing capacity. The H3 Alpha excels both on- and off-road. Also available in combination with the H3^x.

H3^x It's the H3 remixed. A HUMMER that takes its inspiration from the city. With chrome accents, chrome wheels, bright roof rack crossbars and a host of other accessories.

*EPA estimated mpg 14 city/18 highway



2009 H3 TRIM LEVELS

H3 ADVENTURE

Includes a cast iron, fully locking electronic front and rear differentials, 4.03:1 2-speed transfer case, 33-in. LT285/75R16C on-road/off-road tires, in-dash 6-disc CD with 7-speaker Monsoon® sound system.

H3 LUXURY

Automatic transmission, leather-appointed interior, heated front seats with 8-way power adjustment (including lumbar support), leather-wrapped steering wheel, in-dash 6-disc CD changer and premium 7-speaker Monsoon® sound system, fabric cargo cover, front and rear oversized carpeted floor mats.

H3 ALPHA

Vortec 5.3L V8 engine, Hydra-matic 4L60-E 4-speed automatic transmission, leather-appointed interior, heated front seats with 8-way power adjustment (including lumbar support), leather-wrapped steering wheel, in-dash 6-disc CD changer and premium 7-speaker Monsoon® sound system, 16-in. chrome wheels, chrome door handles and mirror caps, universal remote with lighted vanity mirror, fabric cargo cover, rear Alpha tailgate badge, Alpha embroidered headrests, Alpha horn badge, front and rear oversized carpeted floor mats.










Add the off-road suspension option to H3 Luxury or H3 Alpha for the ultimate off-roading experience.

H3^x

Unique square cornered chrome wrap-around brush guard, body color grille, 18-in. chrome wheels, P265/65R18 on-road/off-road tires, body color hard spare tire cover with chrome accent, H3 logo embroidered in front seat headrests. Available unique paint color: Sonoma Red Metallic.

Also includes leather-appointed interior, heated front seats with 8-way power adjustment (including lumbar support), leather-wrapped steering wheel, in-dash 6-disc CD and premium 7-speaker Monsoon® sound system, chrome door handles and chrome mirror caps, chrome tubular assist steps, chrome fuel filler door. Bright roof rack crossbars. Fabric cargo cover. Front and rear oversized carpeted floor mats.

2009 H3 EXTERIOR AND INTERIOR OPTIONS

			01. Black
			02. Birch White
			03. Victory Red
			04. Boulder Gray Metallic
			05. All Terrain Blue
			06. Graphite Metallic
			07. Solar Flare Metallic*
			08. Carbon Black Metallic*
			09. Sonoma Red Metallic (H3 ^x only)
			10. Ebony w/ Pewter Seat Inserts
			11. Ebony w/ Light Cashmere Seat Inserts
			12. Ebony w/ Red Seat Inserts
			13. Ebony w/ Pewter Piping
			14. Ebony w/ Morocco-Toned Seat Inserts and Piping
			15. Light Cashmere w/ Ebony Piping

*premium charge

STANDARD CLOTH SEATING



OPTIONAL LEATHER-APPOINTED SEATING



2009 H3 AND H3 ALPHA TECHNICAL SPECIFICATIONS

	H3	H3 ALPHA
ENGINE		
TYPE	Vortec 3700 3.7L cast-aluminum block and cylinder head	Vortec 5.3L V8 cast-aluminum block and cylinder heads
HORSEPOWER	239 hp @ 5800 rpm (SAE)	300 hp @ 5200 rpm (SAE)
TORQUE	241 lb-ft @ 4600 rpm	320 lb-ft @ 4000 rpm
FUEL INJECTION TYPE	Multi-point sequential fuel injection	Multi-point sequential fuel injection
DISPLACEMENT	223 cu. in.	325 cu. in.
BORE AND STROKE	3.76 x 4.00	3.78 x 3.62
COMPRESSION RATIO	10.0:1	9.9:1
CRAWL RATIO	BASE VEHICLE: 45.1:1 WITH OPTIONAL OFF-ROAD SUSPENSION PACKAGE: 68.9:1	BASE VEHICLE: 33.1:1 WITH OPTIONAL OFF-ROAD SUSPENSION PACKAGE: 51.1:1
FUEL CONSUMPTION (EPA estimate)	MANUAL TRANSMISSION: 14 mpg city/18 mpg highway AUTOMATIC TRANSMISSION: 14 mpg city/18 mpg highway	AUTOMATIC TRANSMISSION: 13 mpg city/16 mpg highway
RECOMMENDED FUEL	Regular unleaded	Regular unleaded
TRANSMISSION		
	Standard 5-speed manual or optional Hydra-Matic 4L60-E 4-speed automatic	Hydra-Matic 4L60-E 4-speed automatic
DRIVETRAIN		
	2-speed, electronically controlled, full-time 4WD	2-speed, electronically controlled, full-time 4WD
TRACTION CONTROL SYSTEM (TCS)		
	Brake-controlled, single-wheel control capability	Brake-controlled, single-wheel control capability
STEERING		
	Power-assisted, rack-and-pinion	Power-assisted, rack-and-pinion
BRAKES		
	Electro-hydraulic power 4-wheel disc, 4-wheel anti-lock, 4-piston opposed fixed front caliper/single-piston sliding rear caliper with Dynamic Rear Proportioning	Electro-hydraulic power 4-wheel disc, 4-wheel anti-lock, 4-piston opposed fixed front caliper/single-piston sliding rear caliper with Dynamic Rear Proportioning
FRONT SUSPENSION		
	Independent SLA torsion bars, 46 mm monotube gas-charged shocks and 36 mm tubular stabilizer bar	Independent SLA torsion bars, 46 mm monotube gas-charged shocks and 36 mm tubular stabilizer bar
REAR SUSPENSION		
	Multi-leaf, semi-elliptic dual-stage leaf spring, 46 mm monotube gas-charged shocks and 25 mm rear stabilizer bar	Multi-leaf, semi-elliptic dual-stage leaf spring, 46 mm monotube gas-charged shocks and 25 mm rear stabilizer bar
FRAME		
	Fully welded steel	Fully welded steel
WHEELS & TIRES		
	16 x 7.5-in. painted aluminum wheels, 32-in. P265/75R16 all-terrain steel-belted tires with full-size spare tire	16 x 7.5-in. thick spoke chrome wheels, 32-in. P265/75R16 all-terrain steel-belted tires with full-size polished spare tire
WEIGHTS & CAPACITIES		
GVWR (lb.) NOTE 1	6,001	6,001
CURB WEIGHT (lb.)	4,695	4,883
PAYLOAD, MAXIMUM (lb.) NOTE 2	1,306	1,118
TRAILERING, MAXIMUM (lb.) NOTE 3	4,500	6,000
FUEL TANK CAPACITY (gal.)	23	23

TECHNICAL SPECIFICATIONS continued

H3 AND H3 ALPHA

EXTERIOR DIMENSIONS (in.)

OVERALL HEIGHT	73.2
OVERALL WIDTH (INCLUDES SIDEVIEW MIRRORS)	85.0
OVERALL LENGTH (WITH REAR TIRE CARRIER) NOTE 4	187.5 (189.5 FOR H3 ³)
WHEELBASE	111.9
OVERHANG	
FRONT	31.6
REAR	44.0
TRACK WIDTH	
FRONT	65.0
REAR	65.5

INTERIOR DIMENSIONS (FIRST-ROW MEASUREMENTS, in.)

HEADROOM (WITHOUT SUNROOF)	40.7
SHOULDER ROOM	54.4
HIP ROOM	53.8
LEGROOM	41.9

CARGO DIMENSIONS **NOTE 5**

LENGTH (BEHIND REAR SEAT, in.)	31.7
WIDTH (AT FLOOR, in.)	42.1
VOLUME (WITH REAR SEAT DOWN, cu. ft.)	62.8

OFF-ROAD CLEARANCES

GROUND CLEARANCE (in.)	
STANDARD 32" TIRES	9.7
OPTIONAL 33" TIRES	10.5
APPROACH ANGLE	
STANDARD 32" TIRES	37.4°
OPTIONAL 33" TIRES	39.0°
DEPARTURE ANGLE NOTE 6	
STANDARD 32" TIRES	34.7°
OPTIONAL 33" TIRES	36.3°
BREAKOVER ANGLE	
STANDARD 32" TIRES	22.1°
OPTIONAL 33" TIRES	23.7°

PERFORMANCE

0-60 MPH: NOTE 7	H3 9.8 sec; H3 ALPHA 8.2 sec.
TURNING CIRCLE:	37 ft.
GRADE CAPABILITY:	60%
SIDE SLOPE CAPABILITY:	40%
WATER FORDING DEPTH:	24 in. @ 5 mph; 16 in. @ 20 mph
VERTICAL SCALING HEIGHT:	16 in.

STANDARD AND OPTIONAL FEATURES

STANDARD INTERIOR EQUIPMENT

Power windows, including "express down" driver window
 Bluetooth® for phone **NOTE 8**
 Power-adjustable driver cloth seat
 Power door locks
 Seating for five
 Cloth seats
 Fold-down 60/40 split rear seat
 Electric rear window defogger
 Manually controlled front air conditioning system with electronic controls
 AM/FM stereo with CD player
 Driver Information Center
 Two 12-volt auxiliary covered power outlets in front; one covered outlet in the rear cargo area
 Rubberized flooring in cargo area
 Five assist handles
 Cruise control
 Electrochromic rearview mirror with 8-point compass, outside temperature display and OnStar controls
 Retained accessory power
 2.64:1 2-speed transfer case

STANDARD EXTERIOR EQUIPMENT

One-piece swing gate with assist strut
 Swing gate mounted full-size spare tire
 Fog lamps
 Dual composite halogen headlamps
 Full underbody protection
 Front and rear recovery hooks
 4-wheel disc brakes with ABS

STANDARD SAFETY AND SECURITY FEATURES

Dual front air bags with Passenger Sensing System **NOTE 9**
 Head curtain side air bags **NOTE 9**
 Remote keyless entry with panic button
 TheftLock™ for radio
 StabiliTrak Electronic Stability Control System
 Traction Control System (TCS)
 Content alarm theft deterrent system
 PASSLock® theft deterrent vehicle security system
 Battery rundown protection
 Rear door child security locks
 LATCH child seat anchors
 Daytime running lamps
 Tire pressure monitoring system (TPM) **NOTE 10**
 Hill Start Assist

OPTIONAL EQUIPMENT

Sliding glass sunroof with "express open" and "express close"
 Hydra-Matic 4L60-E 4-speed automatic transmission (STANDARD ON H3 ALPHA AND H3³)
 Leather-appointed seats
 Chrome Appearance Package (includes door handles and mirror caps)
 Trailer hitch and wiring harness
 16 x 7.5-in. chrome wheels with polished spare
 In-dash 6-disc CD changer with premium 7-speaker Monsoon® sound system
 Off-Road Suspension Package (cast iron fully locking electronic front and rear differential, 4.03:1 2-speed transfer case, 33-in. LT285/75R16C on-road/off-road tires)
 Universal Remote with lighted vanity mirrors
 Rear vision camera system

Learn more at www.HUMMER.com

NOTE 1 When properly equipped, includes weight of vehicle, passengers, cargo, and equipment. **NOTE 2** Maximum payload capacity includes weight of driver, passengers, optional equipment and cargo. **NOTE 3** Maximum trailer weight ratings are calculated assuming a base vehicle, except for any option(s) necessary to achieve the rating, plus driver. The weight of other optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. See your HUMMER dealer for additional details. **NOTE 4** This data applies to models without optional accessories. Consult your HUMMER dealer for dimensions with other optional accessories. **NOTE 5** Cargo and load capacity are limited by weight and distribution. **NOTE 6** This data applies to models without hitch and optional accessories. Consult your HUMMER dealer for dimensions with other optional accessories. **NOTE 7** This data applies to models with an automatic transmission and 32" tires. **NOTE 8** Go to www.gm.com/bluetooth to find out which Bluetooth phones are compatible with the vehicle. **NOTE 9** Always use safety belts and the correct child restraints for your child's age and size. Even in vehicles equipped with Passenger Sensing System, children are safer when properly secured in a rear seat in the appropriate infant, child, or booster seat. Never place a rear-facing infant restraint in the front seat of any vehicle equipped with an active frontal air bag. See the vehicle Owner's Manual and child safety seat instructions for more safety information. **NOTE 10** Does not monitor spare tire.

HUMMER®

PLEASE CALL 1.800.REAL.4WD OR VISIT OUR WEB SITE AT WWW.HUMMER.COM.

IMPORTANT WORDS ABOUT THIS CATALOG We have tried to make this catalog comprehensive and factual. We reserve the right, however, to make changes at any time, without notice, in prices, colors, materials, equipment, specifications, models and availability. Specifications, dimensions, measurements, ratings and other numbers in this catalog and other printed materials provided at the dealership or affixed to vehicles are approximates based upon design and engineering drawings, prototypes and laboratory tests. Your vehicle may differ due to variations in manufacture and equipment. Since some information may have been updated since the time of printing, please check with your HUMMER dealer for complete details. HUMMER reserves the right to lengthen or shorten the model year for any product for any reason or to start and end model years at different times.

ASSEMBLY HUMMER vehicles and their components are assembled or produced by different operating units of General Motors, its subsidiaries or suppliers to GM worldwide. We sometimes find it necessary to produce HUMMER vehicles with different or differently sourced components than originally scheduled. Since some options may be unavailable when your vehicle is assembled, we suggest that you verify that your vehicle includes the equipment you ordered or, if there are changes, that they are acceptable to you.

ENGINES HUMMER products are equipped with engines produced by GM Powertrain or other suppliers to GM worldwide. The engines in HUMMER products may also be used in other GM makes and models.

A NOTE ABOUT CHILD SAFETY Always use safety belts and the correct child restraints for your child's age and size. Children are safer when properly secured in a rear seat in the appropriate infant, child or booster seat. Never place a rear-facing infant restraint in the front seat of any vehicle equipped with an active frontal air bag. See the vehicle Owner's Manual and child safety seat instructions for more safety information.

ADDITIONAL NOTES Monsoon is a registered trademark of Delphi Corporation. PASSLock is a registered trademark of General Motors Corporation. Pictured vehicles may vary from actual production models and may feature optional accessories or equipment. Details and specifications may vary according to local regulations and conditions. The photography in this brochure features the HUMMER in environmentally approved areas for off-road use. H3, H3^X, H3 Alpha, Like Nothing Else and Vortec are trademarks of General Motors Corporation. HUMMER and the vehicle's grille design are registered trademarks of General Motors Corporation. © 2008 General Motors Corporation.