

LET IT LOOSE™

2010

FUSION®

AMMUNITION CATALOG

TOUGH.  
ACCURATE.  
LETHAL.

# TABLE OF CONTENTS

|                                    |     |
|------------------------------------|-----|
| New Products .....                 | 2   |
| Fusion Rifle .....                 | 3-6 |
| Fusion Handgun .....               | 7   |
| Fusion Shotgun .....               | 8   |
| Fusion Muzzleloading Slugs .....   | 9   |
| Fusion Muzzleloading Primers ..... | 9   |
| Fusion Component Bullets .....     | 10  |
| Fusion Gear .....                  | 10  |

## TOUGH. ACCURATE. LETHAL.

Much like a heavyweight fighter on his way to be champion, Fusion® strives to be the best year in and year out. Fusion technology has been honed, programmed and designed for just one thing: deer. And proven performance speaks for itself. Across all disciplines of modern deer hunting, Fusion brings the most dedicated hunters unbelievable toughness and accuracy at an unbeatable price.

Long before he burst on the scene as a NCAA Division I Wrestling National Champion, made his debut as a professional in the ring or conquered the octagon, Brock Lesnar was a hunter. And he had one target that stood out from the rest: whitetails. Every chance he got, Lesnar pursued monster bucks in their favorite haunts on or near the South Dakota farm where he grew up.

The partnership between Lesnar and Fusion isn't some glitzy, gimmicky spokesman agreement where he shows up to sign a few autographs and take a few pictures. This American sportsman's desire to take down the most elusive whitetail bucks means he'll be in the woods rain or shine, sleet or snow. Whatever the conditions, he'll be striving to put another monster in his sights. And when he does, you can bet Fusion will be right there with him.



**Brock Lesnar** The Heavyweight champ trains hard to stay at the top of his sport. He's also no stranger to hunting hard. Lesnar is an avid whitetail hunter and targets the biggest whitetail bucks.

# THE POWER IS IN YOUR HANDS

The world's hottest deer bullet is no longer just pre-loaded for the masses. For 2010, Fusion® rifle and handgun component bullets will be available to handloaders everywhere. These projectiles are the toughest, most accurate in their class. Now hunters have even more control of this power. Choose from a variety of bullet weights and sizes to find your perfect deer hunting load. (See page 10 for more information.)



## CONTINUING TO MEET THE DEMAND

Each year, Fusion® adds product offerings to better round out the lineup. All modern deer hunters can find their ideal options. If you shoot anything from a handgun to a muzzleloader, you'll find what you're after. This year, we add a few more rifle options and another handgun hunting option sure to capture your interest.

# FUSION® RIFLE: KEEPING THE MODERN DEER HUNTER ON TOP

Fusion® technology allowed us to drastically change the way deer ammunition was seen. Before Fusion, there was a big gap in performance between the economical and Premium® loads available to deer hunters. Many times buying the less expensive meant sacrificing a lot of performance in the field. Saving a few dollars may have meant less-than ideal results in the field.

The need to come up with a bullet that is affordable, but can be counted on without fail was met by Fusion. No other bullet in its class is as tough, accurate or lethal.

The Fusion process electrochemically joins the jacket to the core in a way that ensures impressive weight retention. These bullets won't separate—so you know all the energy from these advanced projectiles is transferred on impact—stopping deer in their tracks. This year, look for new offerings in .22-250 Rem., 7mm-08 Rem., 7.62x39mm Soviet and the classic .35 Whelen.



**Brock Lesnar** The toughness both Lesnar and Fusion are known for makes them a great combination and strikes fear into competitors and whitetails alike.

## RIFLE BALLISTICS



| LOAD NO.   | CALIBER               | WEIGHT |       | BULLET STYLE | PRIMER NO. | VELOCITY IN FEET PER SEC. (TO NEAREST 10 FPS) |      |      |      |      | ENERGY IN FOOT POUNDS (NEAREST 5 FOOT POUNDS) |        |      |      |      | WIND DRIFT |      |     |     |     | HEIGHT OF BULLET TRAJECTORY ABOVE OR BELOW LINE OF SIGHT IF ZEROED AT @ YARDS SIGHTS 1.5 INCHES ABOVE BORE LINE |      |               |     |      | TEST BARREL LENGTH |            |     |     |      |       |       |    |
|------------|-----------------------|--------|-------|--------------|------------|---|------|------|------|------|---|--------|------|------|------|------------|------|-----|-----|-----|---|------|---------------|-----|------|--------------------|------------|-----|-----|------|-------|-------|----|
|            |                       | GRAINS | GRAMS |              |            | Muzzle  | 100  | 200  | 300  | 400  | 500   | Muzzle | 100  | 200  | 300  | 400        | 500  | 100 | 200 | 300 | 400   | 500  | AVERAGE RANGE |     |      |                    | LONG RANGE |     |     |      |       |       |    |
|            |                       |        |       |              |            |   |      |      |      |      |   |        |      |      |      |            |      |     |     |     |   |      | 50            | 100 | 200  |                    | 300        | 400 | 500 |      |       |       |    |
| F223FS1    | 223 Rem.              | 62     | 4.02  | Fusion       | 205        | 3000  | 2700 | 2410 | 2150 | 1900 | 1670  | 1240   | 1000 | 800  | 635  | 495        | 385  | 1.0 | 4.0 | 9.7 | 18.1  | 30.4 | -0.2          | @   | -3.3 | -12.6              | 0.6        | 1.6 | @   | -7.7 | -22.8 | -48.0 | 24 |
| F22250FS1  | 22-250 Rem.           | 55     | 3.56  | Fusion       | 210        | 3650  | 2980 | 2410 | 1900 | 1470 | 1160  | 1625   | 1085 | 705  | 440  | 265        | 165  | 1.6 | 6.8 | 17  | 34.3  | 60.6 | -0.3          | @   | -2.5 | -11.1              | 0.3        | 1.2 | @   | -7.4 | -24.9 | -60   | 24 |
| F243FS1    | 243 Win. (6.16x51mm)  | 95     | 6.16  | Fusion       | 210        | 2980  | 2730 | 2490 | 2270 | 2060 | 1850  | 1875   | 1570 | 1310 | 1085 | 890        | 725  | 0.8 | 3.3 | 7.8 | 14.6  | 23.7 | -0.2          | @   | -3.2 | -11.9              | 0.6        | 1.6 | @   | -7.2 | -21.2 | -43.2 | 24 |
| F2506FS1   | 25-06 Rem.            | 120    | 7.78  | Fusion       | 210        | 2980  | 2780 | 2590 | 2400 | 2220 | 2050  | 2365   | 2055 | 1780 | 1535 | 1315       | 1120 | 0.6 | 2.6 | 6.0 | 11.3  | 18.3 | -0.2          | @   | -3.0 | -11.2              | 0.5        | 1.5 | @   | -6.7 | -19.5 | -39.3 | 24 |
| F260FS1    | 260 Rem.              | 120    | 7.78  | Fusion       | 210        | 2950  | 2710 | 2480 | 2270 | 2060 | 1870  | 2320   | 1955 | 1640 | 1370 | 1130       | 930  | 0.8 | 3.3 | 7.6 | 14.2  | 23.0 | -0.2          | @   | -3.2 | -12.1              | 0.6        | 1.6 | @   | -7.3 | -21.4 | -43.4 | 24 |
| F6555FS1   | 6.5x55 Swedish        | 140    | 9.07  | Fusion       | 210        | 2530  | 2340 | 2150 | 1970 | 1800 | 1650  | 1990   | 1695 | 1435 | 1210 | 1010       | 845  | 0.8 | 3.6 | 8.3 | 15.3  | 25.3 | 0.0           | @   | -4.9 | -17.4              | 1.2        | 2.5 | @   | -9.9 | -28.7 | -58.7 | 24 |
| F270FS1    | 270 Win.              | 130    | 8.42  | Fusion       | 210        | 3050  | 2810 | 2580 | 2370 | 2160 | 1970  | 2685   | 2280 | 1925 | 1620 | 1350       | 1115 | 0.7 | 3.0 | 7.0 | 13.1  | 21.3 | -0.2          | @   | -2.9 | -11.0              | 0.5        | 1.5 | @   | -6.6 | -19.6 | -39.8 | 24 |
| F270FSLR1  | 270 Win.              | 145    | 9.40  | Fusion       | 210        | 2200  | 2010 | 1830 | -    | -    | -   | 1560   | 1295 | 1070 | -    | -          | -    | 1.1 | 4.6 | -   | -   | -    | 0.2           | @   | -7.1 | -                  | -          | -   | -   | -    | -     | 24    |    |
| F270FS2    | 270 Win.              | 150    | 9.72  | Fusion       | 210        | 2850  | 2660 | 2470 | 2290 | 2120 | 1950  | 2705   | 2345 | 2030 | 1745 | 1495       | 1270 | 0.7 | 2.8 | 6.5 | 12.0  | 19.3 | -0.2          | @   | -3.4 | -12.6              | 0.7        | 1.7 | @   | -7.4 | -21.6 | -43.3 | 24 |
| F270WSMFS1 | 270 Win. Short Magnum | 150    | 9.72  | Fusion       | 215        | 3060  | 2870 | 2680 | 2500 | 2330 | 2170  | 3120   | 2735 | 2395 | 2090 | 1815       | 1565 | 0.5 | 2.4 | 5.5 | 10.0  | 16.3 | -0.3          | @   | -2.8 | -10.3              | 0.4        | 1.4 | @   | -6.2 | -17.9 | -36.1 | 24 |
| F708FS2    | 7mm-08 Rem.           | 120    | 7.78  | Fusion       | 210        | 3000  | 2720 | 2460 | 2210 | 1970 | 1750  | 2400   | 1970 | 1605 | 1295 | 1035       | 820  | 0.9 | 3.7 | 8.8 | 16.5  | 27.3 | -0.2          | @   | -3.2 | -12.2              | 0.6        | 1.6 | @   | -7.4 | -22   | -45.6 | 24 |
| F708FS1    | 7mm-08 Rem.           | 140    | 9.07  | Fusion       | 210        | 2850  | 2620 | 2390 | 2180 | 1980 | 1790  | 2525   | 2125 | 1780 | 1480 | 1220       | 995  | 0.9 | 3.4 | 8.0 | 14.9  | 24.3 | -0.2          | @   | -3.6 | -13.3              | 0.7        | 1.8 | @   | -7.9 | -23.2 | -47.2 | 24 |
| F280FS1    | 280 Rem.              | 140    | 9.07  | Fusion       | 210        | 2990  | 2790 | 2610 | 2430 | 2260 | 2090  | 2780   | 2425 | 2115 | 1830 | 1580       | 1355 | 0.6 | 2.5 | 5.8 | 10.7  | 17.5 | -0.2          | @   | -3.0 | -11.0              | 0.5        | 1.5 | @   | -6.5 | -19.1 | -38.5 | 24 |
| F7RFS1     | 7mm Rem. Magnum       | 150    | 9.72  | Fusion       | 215        | 3050  | 2860 | 2680 | 2510 | 2340 | 2180  | 3100   | 2725 | 2390 | 2090 | 1820       | 1580 | 0.5 | 2.3 | 5.4 | 9.8   | 16.0 | -0.3          | @   | -2.8 | -10.4              | 0.4        | 1.4 | @   | -6.2 | -17.9 | -36.1 | 24 |
| F7RFS2     | 7mm Rem. Magnum       | 175    | 11.34 | Fusion       | 215        | 2760  | 2590 | 2430 | 2270 | 2120 | 1980  | 2960   | 2610 | 2295 | 2010 | 1750       | 1520 | 0.7 | 2.5 | 5.8 | 10.8  | 17.4 | -0.1          | @   | -3.6 | -13.2              | 0.8        | 1.8 | @   | -7.8 | -22.3 | -44.5 | 24 |
| F7WSMFS1   | 7mm Win. Short Magnum | 150    | 9.72  | Fusion       | 215        | 3100  | 2910 | 2730 | 2560 | 2390 | 2230  | 3200   | 2820 | 2480 | 2175 | 1900       | 1650 | 0.5 | 2.2 | 5.2 | 9.5   | 15.4 | -0.3          | @   | -2.6 | -9.9               | 0.4        | 1.3 | @   | -6.0 | -17.2 | -34.7 | 24 |

These trajectory tables were calculated by computer using the best available data for each load. Trajectories are representative of the nominal behavior of each load at standard conditions (59°F temperature; barometric pressure of 29.53 inches; altitude at sea level).

Shooters are cautioned that actual trajectories may differ due to variations in altitude, atmospheric conditions, guns, sights and ammunition.

# RIFLE BALLISTICS CONTINUED

NEW!

| LOAD NO.   | CALIBER                   | WEIGHT |       | BULLET STYLE | PRIMER NO. | VELOCITY IN FEET PER SEC. (TO NEAREST 10 FPS) |      |      |      |      |      | ENERGY IN FOOT POUNDS (NEAREST 5 FOOT POUNDS) |      |      |      |      | WIND DRIFT |     |     |      |      | HEIGHT OF BULLET TRAJECTORY ABOVE OR BELOW LINE OF SIGHT IF ZEROED AT 0 YARDS SIGHTS 1.5 INCHES ABOVE BORE LINE |               |     |       |       |     |            |     |       |       | TEST BARREL LENGTH |     |
|------------|---------------------------|--------|-------|--------------|------------|---|------|------|------|------|------|---|------|------|------|------|------------|-----|-----|------|------|---|---------------|-----|-------|-------|-----|------------|-----|-------|-------|--------------------|-----|
|            |                           | GRAINS | GRAMS |              |            | Muzzle  | 100  | 200  | 300  | 400  | 500  | Muzzle  | 100  | 200  | 300  | 400  | 500        | 100 | 200 | 300  | 400  | 500   | AVERAGE RANGE |     |       |       |     | LONG RANGE |     |       |       |                    |     |
|            |                           |        |       |              |            |   |      |      |      |      |      |   |      |      |      |      |            |     |     |      |      |   | 50            | 100 | 200   | 300   | 50  | 100        | 200 | 300   | 400   |                    | 500 |
| F76239FS1  | 7.26x39mm Soviet          | 123    | 9.79  | Fusion       | 210        | 2350  | 2080 | 1820 | 1590 | 1390 | 1220 | 1510  | 1180 | 905  | 695  | 525  | 405        | 1.5 | 6   | 14.8 | 27.7 | 45.9  | 0.1           | ⊕   | -6.5  | -23.8 | 1.8 | 3.3        | ⊕   | -14   | -41.6 | -87.7              | 24  |
| F3030FS1   | 30-30 Win.                | 150    | 9.72  | Fusion       | 210        | 2390  | 2090 | 1810 | 1550 | 1340 | 1170 | 1900  | 1450 | 1085 | 805  | 595  | 455        | 1.6 | 6.6 | 16.2 | 30.8 | 51.1  | 0.1           | ⊕   | -6.5  | -23.9 | 1.7 | 3.2        | ⊕   | -14.2 | -42.8 | -91.5              | 24  |
| F3030FS2   | 30-30 Win.                | 170    | 11.02 | Fusion       | 210        | 2200  | 1950 | 1720 | 1510 | 1330 | 1180 | 1825  | 1435 | 1115 | 860  | 665  | 525        | 1.4 | 6.3 | 15.1 | 28.5 | 46.7  | 0.3           | ⊕   | -7.7  | -27.2 | 2.2 | 3.9        | ⊕   | -15.6 | -46.8 | -97.8              | 24  |
| F308FS1    | 308 Win. (7.62x51mm)      | 150    | 9.72  | Fusion       | 210        | 2820  | 2600 | 2390 | 2190 | 2000 | 1820 | 2650  | 2250 | 1905 | 1600 | 1335 | 1105       | 0.8 | 3.2 | 7.6  | 14.1 | 22.9  | -0.2          | ⊕   | -3.6  | -13.4 | 0.7 | 1.8        | ⊕   | -8.0  | -23.1 | -46.9              | 24  |
| F308FS2    | 308 Win. (7.62x51mm)      | 165    | 10.69 | Fusion       | 210        | 2700  | 2500 | 2310 | 2130 | 1950 | 1790 | 2670  | 2290 | 1955 | 1660 | 1400 | 1175       | 0.7 | 3.1 | 7.5  | 13.7 | 22.3  | -0.1          | ⊕   | -4.1  | -14.7 | 0.9 | 2.0        | ⊕   | -8.6  | -24.8 | -50.1              | 24  |
| F308FSLR1  | 308 Win. (7.62x51mm)      | 170    | 11.02 | Fusion       | 210        | 2000  | 1740 | 1510 | -    | -    | -    | 1510  | 1145 | 860  | -    | -    | -          | 1.9 | 8.1 | -    | -    | -   | 0.5           | ⊕   | -10.0 | -     | -   | -          | -   | -     | -     | -                  | 24  |
| F308FS3    | 308 Win. (7.62x51mm)      | 180    | 11.66 | Fusion       | 210        | 2600  | 2430 | 2260 | 2100 | 1950 | 1800 | 2700  | 2355 | 2040 | 1765 | 1515 | 1295       | 0.6 | 2.9 | 6.9  | 12.6 | 20.4  | -0.1          | ⊕   | -4.4  | -15.7 | 1.0 | 2.2        | ⊕   | -9.1  | -25.8 | -51.9              | 24  |
| F3006FS1   | 30-06 Spring. (7.62x63mm) | 150    | 9.72  | Fusion       | 210        | 2900  | 2670 | 2460 | 2250 | 2060 | 1870 | 2800  | 2380 | 2015 | 1695 | 1410 | 1170       | 0.8 | 3.1 | 7.4  | 13.7 | 22.2  | -0.2          | ⊕   | -3.4  | -12.5 | 0.7 | 1.7        | ⊕   | -7.5  | -21.8 | -44.1              | 24  |
| F3006FS2   | 30-06 Spring. (7.62x63mm) | 165    | 10.69 | Fusion       | 210        | 2790  | 2590 | 2400 | 2220 | 2040 | 1880 | 2850  | 2460 | 2110 | 1800 | 1525 | 1285       | 0.8 | 2.9 | 7.0  | 12.9 | 20.7  | -0.1          | ⊕   | -3.7  | -13.4 | 0.8 | 1.8        | ⊕   | -7.9  | -22.9 | -46.0              | 24  |
| F3006FS3   | 30-06 Spring. (7.62x63mm) | 180    | 11.66 | Fusion       | 210        | 2700  | 2520 | 2350 | 2190 | 2030 | 1870 | 2915  | 2540 | 2205 | 1905 | 1640 | 1405       | 0.7 | 2.7 | 6.6  | 12.1 | 19.4  | -0.1          | ⊕   | -4.0  | -14.3 | 0.9 | 2.0        | ⊕   | -8.4  | -23.9 | -47.8              | 24  |
| F3006FSLR1 | 30-06 Spring. (7.62x63mm) | 170    | 11.02 | Fusion       | 210        | 2000  | 1740 | 1510 | -    | -    | -    | 1510  | 1145 | 860  | -    | -    | -          | 1.9 | 8.1 | -    | -    | -   | 0.5           | ⊕   | -10.0 | -     | -   | -          | -   | -     | -     | -                  | 24  |
| F300WFS1   | 300 Win. Magnum           | 150    | 9.72  | Fusion       | 215        | 3200  | 2960 | 2730 | 2510 | 2300 | 2110 | 3410  | 2915 | 2480 | 2100 | 1770 | 1480       | 0.6 | 2.7 | 6.4  | 11.8 | 19.4  | -0.3          | ⊕   | -2.5  | -9.6  | 0.3 | 1.2        | ⊕   | -5.9  | -17.3 | -35.4              | 24  |
| F300WFS2   | 300 Win. Magnum           | 165    | 10.69 | Fusion       | 215        | 3080  | 2870 | 2660 | 2460 | 2280 | 2100 | 3475  | 3005 | 2590 | 2225 | 1900 | 1610       | 0.6 | 2.6 | 6.1  | 11.2 | 18.3  | -0.3          | ⊕   | -2.8  | -10.4 | 0.4 | 1.4        | ⊕   | -6.3  | -18.3 | -37.1              | 24  |
| F300WFS3   | 300 Win. Magnum           | 180    | 11.66 | Fusion       | 215        | 2960  | 2770 | 2580 | 2400 | 2230 | 2070 | 3500  | 3055 | 2660 | 2305 | 1985 | 1705       | 0.6 | 2.6 | 5.9  | 10.9 | 17.7  | -0.2          | ⊕   | -3.1  | -11.3 | 0.6 | 1.5        | ⊕   | -6.7  | -19.5 | -39.4              | 24  |
| F300WSMFS3 | 300 Win. Short Magnum     | 150    | 9.72  | Fusion       | 215        | 3250  | 3010 | 2770 | 2560 | 2350 | 2150 | 3520  | 3010 | 2565 | 2175 | 1830 | 1535       | 0.6 | 2.7 | 6.3  | 11.6 | 18.9  | -0.3          | ⊕   | -2.4  | -9.3  | 0.3 | 1.2        | ⊕   | -5.7  | -16.7 | -34.2              | 24  |
| F300WSMFS1 | 300 Win. Short Magnum     | 165    | 10.69 | Fusion       | 215        | 3100  | 2890 | 2680 | 2480 | 2300 | 2120 | 3520  | 3050 | 2630 | 2260 | 1930 | 1640       | 0.6 | 2.6 | 6.0  | 11.1 | 18.1  | -0.3          | ⊕   | -2.7  | -10.2 | 0.4 | 1.4        | ⊕   | -6.2  | -18.0 | -36.5              | 24  |
| F300WSMFS2 | 300 Win. Short Magnum     | 180    | 11.66 | Fusion       | 215        | 2950  | 2760 | 2570 | 2390 | 2220 | 2060 | 3480  | 3035 | 2640 | 2285 | 1970 | 1690       | 0.6 | 2.6 | 5.9  | 11.0 | 17.9  | -0.2          | ⊕   | -3.1  | -11.4 | 0.6 | 1.5        | ⊕   | -6.8  | -19.7 | -39.7              | 24  |
| F338FS1    | 338 Win. Magnum           | 225    | 14.58 | Fusion       | 215        | 2850  | 2690 | 2530 | 2370 | 2220 | 2080 | 4060  | 3600 | 3190 | 2810 | 2470 | 2165       | 0.6 | 2.3 | 5.3  | 9.9  | 15.9  | -0.2          | ⊕   | -3.3  | -12.0 | 0.7 | 1.7        | ⊕   | -7.1  | -20.4 | -40.8              | 24  |
| F338FFS2   | 338 Federal               | 200    | 12.96 | Fusion       | 210        | 2700  | 2490 | 2280 | 2090 | 1910 | 1730 | 3235  | 2745 | 2315 | 1940 | 1610 | 1335       | 0.8 | 3.4 | 8.1  | 14.8 | 24.4  | -0.1          | ⊕   | -4.1  | -15.0 | 0.9 | 2.1        | ⊕   | -8.8  | -25.3 | -51.9              | 24  |
| F35FS1     | 35 Whelen                 | 180    | 11.66 | Fusion       | 210        | 2700  | 2420 | 2160 | 1910 | 1690 | 1480 | 2915  | 2340 | 1860 | 1460 | 1135 | 880        | 1.1 | 4.7 | 11   | 21   | 34.8  | -0.1          | ⊕   | -4.5  | -16.4 | 1.0 | 2.2        | ⊕   | -9.6  | -29.1 | -60.7              | 24  |
| F4570FS1   | 45-70 Government          | 300    | 19.44 | Fusion       | 210        | 1850  | 1610 | 1400 | 1230 | 1100 | 1010 | 2280  | 1730 | 1305 | 1005 | 805  | 680        | 2.3 | 8.7 | 20.6 | 37.6 | 59.3  | 0.7           | ⊕   | -11.9 | -41.6 | 3.7 | 5.9        | ⊕   | -23.8 | -70.9 | -146.5             | 24  |

NEW!

These trajectory tables were calculated by computer using the best available data for each load. Trajectories are representative of the nominal behavior of each load at standard conditions (59°F temperature; barometric pressure of 29.53 inches; altitude at sea level).

Shooters are cautioned that actual trajectories may differ due to variations in altitude, atmospheric conditions, guns, sights and ammunition.

## FUSION® RIFLE: THIS LITE® STILL HITS PLENTY HARD

| LOAD NO.   | CALIBER                   | WEIGHT |       | BULLET STYLE | PRIMER NO. | VELOCITY IN FEET PER SEC. (TO NEAREST 10 FPS) |      |      |     |     |     |
|------------|---------------------------|--------|-------|--------------|------------|---|------|------|-----|-----|-----|
|            |                           | GRAINS | GRAMS |              |            | Muzzle  | 100  | 200  | 300 | 400 | 500 |
| F270FSLR1  | 270 Win.                  | 145    | 9.40  | Fusion       | 210        | 2200  | 2010 | 1830 | -   | -   | -   |
| F308FSLR1  | 308 Win. (7.62x51mm)      | 170    | 11.02 | Fusion       | 210        | 2000  | 1740 | 1510 | -   | -   | -   |
| F3006FSLR1 | 30-06 Spring. (7.62x63mm) | 170    | 11.02 | Fusion       | 210        | 2000  | 1740 | 1510 | -   | -   | -   |

Fusion Lite® offerings give shooters who prefer less recoil an effective option in the field. These loads don't feature ultra-light bullets—just half the recoil. They're effective out to 200 yards and the same deer-dropping technology Fusion is known for goes into these special loads. These lower velocity offerings in the most popular calibers are excellent choices for new shooters or those who prefer the lighter recoil. With standard bullet weights and half the recoil, you'll be ultra-comfortable behind your favorite deer rifle. That's good news for you and bad news for that monster whitetail you're after.

### FUSION LITE® VS. FUSION® HALF THE RECOIL

**FUSION LITE®**  
30-06 170 GR.

**FUSION®**  
30-06 180 GR.

0 15 30  
FT. LBS.

# FUSION® HANDGUN: AN EXACT SCIENCE



Fusion® handgun loads are another product in the Fusion fold specifically designed for hunting whitetails. No details are overlooked. The bullet construction is exactly the same as their centerfire rifle counterparts for excellent toughness. In addition, velocities and recoils are intended for use in the field. We understand that super fast loads might look good on paper, but real-world recoil means inaccurate shooting and missed trophies. For this reason, bullet weights and velocities have been developed to be lethal on whitetails, without pounding the shooter. Look for one of these new loads in the .500 S&W this fall.

## HANDGUN BALLISTICS

| LOAD NO. | CALIBER        | WEIGHT |        | BULLET-STYLE | PRIMER NO. | VELOCITY IN FEET PER SEC. (TO NEAREST 10 FPS) |      |      |      |      | ENERGY IN FOOT POUNDS (NEAREST 5 FOOT POUNDS) |      |      |      |     | TRAJECTORY (SIGHTS .9 INCHES ABOVE BORE LINE) |      |      |      | TEST BARREL |
|----------|----------------|--------|--------|--------------|------------|---|------|------|------|------|---|------|------|------|-----|---|------|------|------|-------------|
|          |                | Grains | Grains |              |            | Muzzle  | 25   | 50   | 75   | 100  | Muzzle  | 25   | 50   | 75   | 100 | 25  | 50   | 75   | 100  |             |
| F357FS1  | 357 Magnum     | 158    | 10.24  | Fusion       | 100        | 1240  | 1190 | 1140 | 1100 | 1060 | 540   | 495  | 455  | 425  | 395 | ⊕   | -0.6 | -3.0 | -7.1 | 4-V         |
| F41FS1   | 41 Rem. Magnum | 210    | 13.61  | Fusion       | 150        | 1230  | 1170 | 1120 | 1080 | 1040 | 705   | 640  | 585  | 545  | 505 | ⊕   | -0.7 | -3.1 | -7.3 | 4-V         |
| F44FS1   | 44 Rem. Magnum | 240    | 15.55  | Fusion       | 150        | 1290  | 1220 | 1160 | 1110 | 1070 | 885   | 795  | 720  | 655  | 605 | ⊕   | -0.6 | -2.7 | -6.7 | 4-V         |
| F454FS1  | 454 Casull     | 260    | 16.85  | Fusion       | 150        | 1350  | 1270 | 1190 | 1130 | 1080 | 1050  | 925  | 820  | 735  | 670 | ⊕   | -0.5 | -2.4 | -6.1 | 5.7-V       |
| F460FS1  | 460 S&W        | 260    | 16.85  | Fusion       | 210        | 1600  | 1500 | 1400 | 1310 | 1230 | 1480  | 1290 | 1125 | 990  | 870 | ⊕   | -0.1 | -1.3 | -3.7 | 8.4-V       |
| F500FS2  | 500 S&W        | 325    | 21.06  | Fusion       | 210        | 1450  | 1360 | 1270 | 1200 | 1130 | 1515  | 1330 | 1170 | 1035 | 930 | ⊕   | -0.3 | -1.9 | -5   | 8.4-V       |

V = Vented Barrel

These trajectory tables were calculated by computer using the best available data for each load. Trajectories are representative of the nominal behavior of each load at standard conditions (59°F temperature; barometric pressure of 29.53 inches; altitude at sea level). Shooters are cautioned that actual trajectories may differ due to variations in altitude, atmospheric conditions, guns, sights and ammunition.

# FUSION® SHOTGUN SLUGS: BRING A NEW LEVEL OF TOUGHNESS TO YOUR SHOTGUN

The creation of Fusion® shotgun slugs has made shotgunners a part of this deer-optimized technology. Now you can find the same unequalled energy and deer devastation in your favorite rifle-bore shotgun. From a stand or on the move in the field, be the most effective shotgunner in the woods.

## SHOTGUN SLUG BALLISTICS

| LOAD NO.             | GAUGE | SHELL LENGTH |    | SLUG TYPE         | SLUG WEIGHT |        | VELOCITY IN FEET PER SECOND (TO NEAREST 10 FPS) |      |      |    |      |      |      |      | ENERGY IN FOOT-POUNDS (To nearest 5 foot-pounds) |        |      |      |      |      |      |      | TRAJECTORY (SIGHTS .5 INCHES ABOVE BORE LINE.) |      |     |     | TEST BARREL |     |     |      |      |       |       |    |
|----------------------|-------|--------------|----|-------------------|-------------|--------|---|------|------|----|------|------|------|------|--|--------|------|------|------|------|------|------|--|------|-----|-----|-------------|-----|-----|------|------|-------|-------|----|
|                      |       | Inches       | MM |                   | Ounces      | Grains | Muzzle  | 25   | 50   | 75 | 100  | 125  | 150  | 175  | 200  | Muzzle | 25   | 50   | 75   | 100  | 125  | 150  | 175  | 200  | 25  | 50  |             | 75  | 100 | 125  | 150  | 175   | 200   |    |
| <b>NEW!</b> F151 FS2 | 12    | 3            | 76 | Fusion Sabot Slug | 7/8         | 383    | 1700  | 1600 | 1500 |    | 1410 | 1320 | 1250 | 1180 | 1120   | 1070   | 2455 | 2165 | 1905 | 1680 | 1485 | 1320 | 1180   | 1070 | 980 | 1.0 | 1.7         | 1.4 | ⊕   | -2.6 | -6.7 | -12.3 | -19.6 | 30 |
| <b>NEW!</b> F154 FS2 | 12    | 2-3/4        | 70 | Fusion Sabot Slug | 7/8         | 383    | 1600  | 1500 | 1410 |    | 1330 | 1250 | 1180 | 1120 | 1080   | 1040   | 2175 | 1915 | 1685 | 1490 | 1325 | 1185 | 1075   | 985  | 910 | 1.2 | 2.0         | 1.6 | ⊕   | -3.0 | -7.5 | -13.8 | -21.9 | 30 |
| <b>NEW!</b> F209 FS2 | 20    | 3            | 76 | Fusion Sabot Slug | 7/8         | 383    | 1550  | 1440 | 1340 |    | 1250 | 1180 | 1110 | 1060 | 1020   | 980    | 2040 | 1765 | 1530 | 1335 | 1175 | 1055 | 955  | 880  | 820 | 1.4 | 2.2         | 1.8 | ⊕   | -3.3 | -8.4 | -15.4 | -24.4 | 30 |
| <b>NEW!</b> F208 FS2 | 20    | 2-3/4        | 70 | Fusion Sabot Slug | 7/8         | 383    | 1450  | 1350 | 1260 |    | 1180 | 1120 | 1070 | 1020 | 990  | 950    | 1785 | 1550 | 1350 | 1190 | 1065 | 965  | 885  | 825  | 770 | 1.6 | 2.5         | 2   | ⊕   | -3.8 | -9.4 | -17.1 | -26.9 | 30 |

# FUSION® MUZZLELOADING SLUGS: FRONT LOADING, BUCK-STOPPING

The late season is a great opportunity to get that wary buck. With the right scouting, you'll get your opportunity. Harness the energy of Fusion® in these accurate muzzle-loader sabot slugs. Fusion technology gives 50-caliber crush-rib sabots reason to seat themselves at the breech of your T/C. The energy has spread to a 50-caliber concoction that uses the same superior technology that makes all Fusion projectiles the most accurate and deadly deer ammunition in their class. A deep snow buck has called your number. Get in the game.



## MUZZLELOADING SLUGS

| FIREARM              | LOAD NO. | CALIBER | WEIGHT GRAINS |
|----------------------|----------|---------|---------------|
| IN-LINE MUZZLELOADER | F50FSML1 | 50      | 240           |
| IN-LINE MUZZLELOADER | F50FSML2 | 50      | 260           |
| IN-LINE MUZZLELOADER | F50FSML3 | 50      | 300           |

# FUSION® PRIMERS: IGNITION YOU CAN COUNT ON

No ignition. No trophy. The Fusion® muzzleloader primer is especially formulated for the tough conditions faced in the late season. Soaking wet. Cold and crisp. Fusion primers ignite no matter what. We worked with muzzleloader gurus Thompson Center Arms to develop the ultimate muzzleloader primer.

## MUZZLELOADING PRIMERS

| FIREARM              | LOAD NO. | DESCRIPTION              |
|----------------------|----------|--------------------------|
| IN-LINE MUZZLELOADER | F209FSML | 209 MUZZLELOADING PRIMER |

# FUSION® COMPONENT BULLETS: NOT JUST FACTORY-LOADED FUN ANYMORE



Fusion® centerfire rifle and handgun hunting ammunition has carved out a loyal base of whitetail enthusiasts. These youthful, aggressive hunters have embraced this advanced technology at a great price. Their ammunition performs every time.

Fusion's following has now created a demand for component bullets. Those hunters that load their own want to be able to utilize these reliable, advanced and affordable projectiles. In response to this, we offer an initial lineup that includes popular bullet weights and diameters for rifle and handgun hunters. Take the power of Fusion ammunition and capture it in your very own hunting loads with these tough boat-tailed bullets.

# IT'S ALL ABOUT ATTITUDE

Find the latest Fusion® gear here or on the web. Look and feel good in the field or on the town. Order your gear today.

## LONG SLEEVE ORANGE THERMAL SHIRT

Vintage long sleeve thermal T-shirt.  
**SIZE:** Medium, Large, XLarge, 2XLarge, 3XLarge  
**PRICE:** \$18.00

## LADIES ORANGE SHIRT

Ladies short sleeve "burned out" tee, with a longer cut and cap sleeve.  
**SIZE:** Small, Medium, Large, XLarge  
**PRICE:** \$16.00

## FUSION CAP

Twill structured Black Cap, Velcro® closure.  
**SIZE:** One Size  
**PRICE:** \$10.00

## SKULL CAP

Fitted cap with embroidered logo.  
**SIZE:** One Size  
**PRICE:** \$10.00

## MEN'S BLACK T-SHIRT

Mineral washed tee, 100% cotton.  
**SIZE:** Medium, Large, XLarge, 2XLarge, 3XLarge  
**PRICE:** \$10.00



To place orders by mail, send completed order form with payment to:  
 OMCM Embroidery & Design, Inc.  
 2355 Station Parkway NW  
 Anoka, MN 55304

Tel: 877-872-7006 Fax: 763-767-2961

Email: [customerservice@omcmembroidery.com](mailto:customerservice@omcmembroidery.com)

FOR ORDER FORMS AND COMPLETE S&H INFORMATION please visit

[www.fusionammo.com](http://www.fusionammo.com)

(All Shipments are restricted to the continental U.S. Sorry no C.O.D orders accepted. Please allow 4-6 weeks for delivery)



## COMMERCIAL PRODUCTS

ATK Commercial Products features a unique collection of brands that gives shooting and outdoor enthusiasts everything they need in one place. From ammunition,

optics and reloading equipment to gun cleaning chemicals and accessories, we offer advanced, high-performance products. Look for these leading brands:

### Ammunition Brands



### Accessories Brands



We proudly support: Ducks Unlimited, Pheasants Forever, The National Wild Turkey Federation, The Rocky Mountain Elk Foundation, Safari Club International, Delta Waterfowl, Izaak Walton League of America, Whitetails Unlimited, The Ruffed Grouse Society, Becoming an Outdoors Woman, Women in The Outdoors, 4-H Shooting Sports Program, The Boy Scouts of America, International Hunter Education Association and Civilian Marksmanship Program, The Congressional Sportsmen Foundation and the NRA.

Federal Cartridge Co. • 900 Ehlen Drive • Anoka, MN 55303  
© 2010 F.C.C. • Printed in U.S.A.

For technical questions call Product Service 1-800-322-2342 • [www.fusionammo.com](http://www.fusionammo.com)

Fusion is a trademark registered with the U.S. Patent Office.