

American Security



Gun Safe Catalog
2009



**American Security Corporate Headquarters
Fontana CA, USA**



Since 1948 American Security Products has protected the assets of our clients throughout the world by providing a broad array of safes and consulting services with the highest degree of quality, integrity and responsiveness. Customers have trusted AMSEC safes for generations. The design of each AMSEC safe draws on over 60 years of experience on protecting the physical assets of our customers. There aren't many criminals with over 60 years of experience, so we think that gives us the advantage.

Before the American Security name is attached, each safe must undergo a rigid 28-point inspection. In addition, every AMSEC safe undergoes the industry's most comprehensive testing program. AMSEC uses independent agencies such as Underwriter's Laboratories to put our designs to the test. We maintain the tightest tolerances and highest standards of fit and finish in the industry.

Our commitment doesn't end there. We have built our company on the commitment to offer the best service in the industry which will insure that AMSEC remains the industry leader.

Our corporate center is staffed with highly trained Customer Service Representatives and our Service Department is supported by 7,500 factory-trained technicians throughout the world. Technicians are available 24 hours a day, 365 days a year to answer questions and help solve problems with any safe shipped anywhere in the world. We have been providing safes and security solutions to the banking industry since 1948. This type of high security technology is built right into our gun safes.

We produce over 60,000 safes each year and we take protecting our customers' assets very seriously. That's how we got to be the largest security safe manufacturer in the world, and that's why you can't buy a better gun safe than an American Security safe.

Simply put, our reputation is built on product design, innovative technology and the best support in the industry.

It has worked for us for over 60 years and it ensures our complete customer satisfaction. The choice is easy:

American Security

The Industry Leader for Over 60 Years

We Stand Behind Our Craftsmanship with a "No Cost" Lifetime Warranty

American Security Products Co. is highly acclaimed for offering the industry's best fire protection. We manufacture the industry's broadest gamut of fire-rated products ranging from Underwriters Laboratories (U.L.) Listed 1 and 2 hour fire safes to our Mercury Class I, Class II, Class III, and Class IV fire protected gun safes.



Actual American Security Safe after a fire.

Fire Protection Level Chart

Each AMSEC safe is designed to maintain an interior temperature of less than 350°F. Paper products will char at approximately 450°F.

Series	Fire Label	Outside Temp	Time Period	Inside Temp Less Than
RF6528	Mercury Level IV	1850°F	120 min.	350°F
HS Series	Mercury Level IV	1850°F	120 min.	350°F
BF® Series	Mercury Level III	1275°F	90 min.	350°F
SF Series	Mercury Level II	1200°F	60 min.	350°F
TF Series	Mercury Level I	1200°F	30 min.	350°F



AMSEC gun safes that proudly display the UL Residential Security Container (RSC) Burglary Classification demonstrated the ability to withstand rigorous prying, drilling, punching, hammering, chiseling and tampering attacks performed by today's most experienced UL expert technicians.



Most of our Gun Safes meet or exceed the standards for California approved Firearms Safety devices and the requirements of California Penal Code Section 12088, Gun Safe Standards. Look for our DOJ Approved Label.



All of our HS, BF, SF and TF Series safes come with a Palusol Intumescent Door Seal. When the intumescent seal is exposed to high temperature (above 250°F), it expands to as much as 8 times its original thickness. This provides a strong positive seal between the door and body, preventing heat influx.

Gun Safe Lifetime Warranty

IF YOU ARE THE ORIGINAL OWNER OF AN AMSEC GUN SAFE THAT SUFFERS DAMAGE DUE TO THEFT OR FIRE, PROVIDE US WITH A PROPERLY FILED POLICE REPORT, WITHIN 30 DAYS. WITH ABSOLUTELY NO COST TO YOU, WHICH MEANS: FREE PARTS, FREE LABOR AND FREE FREIGHT; WE WILL EITHER REPAIR OR REPLACE (OUR OPTION) WITH A CURRENT PRODUCTION MODEL OF COMPARABLE VALUE. FOR ADDITIONAL ASSISTANCE, PLEASE CONTACT YOUR LOCAL DEALER. WE WILL BE STANDING BY READY TO TAKE IMMEDIATE ACTION TO GET YOUR VALUABLES QUICKLY SECURED BACK IN A QUALITY BUILT AMSEC SAFE.

NO COST - BREAK-IN WARRANTY

IF YOUR AMSEC GUN SAFE IS FORCIBLY ENTERED, WE WILL REPLACE OR REPAIR IT, FREE OF CHARGE.

NO COST - ATTEMPTED BREAK-IN WARRANTY

IF YOUR AMSEC GUN SAFE HAS BEEN SUBJECT TO A DRILL, PUNCH OR PRY ATTACK AND HAS PERFORMED SUCCESSFULLY BY KEEPING THE INTRUDERS OUT, IT WILL BE REPAIRED OR REPLACED FREE OF CHARGE.

NO COST - FIRE WARRANTY

IF YOUR AMSEC GUN SAFE HAS BEEN SUBJECT TO A HOME FIRE, IT WILL BE REPAIRED OR REPLACED FREE OF CHARGE.

AMERICAN SECURITY'S WARRANTY COMMITMENT TO YOU: WE WILL FIX THE SAFE IN YOUR HOME IF AT ALL POSSIBLE. WE WILL PAY FOR THE SAFE TECHNICIAN TO OPEN THE SAFE. WE WILL PAY FOR THE SAFE TECHNICIAN TO REPAIR THE SAFE AND IF A REPAIR IS NOT POSSIBLE WITHIN THE HOME, WE WILL PAY FOR THE FREIGHT BACK TO THE FACTORY. EFFECTIVE ON GUN SAFE PURCHASES STARTING 01/01/2006

Contents

HS Series	
<i>High Security</i>	4
BF® Series	
<i>Burglary/Fire</i>	6
SF Series	
<i>Sixty Minute Fire</i>	8
TF Series	
<i>Thirty Minute Fire</i>	10
Home Safes	12
Handgun Safes	13
Security Products	14
Vault Door	15
Storage Options	16
Other Options	17
Features At A Glance	18



The RF6528 Features:

The only U.L. Listed TL-30 burglary and fire resistant gun safe on the market.

2¾" thick door constructed of outer and inner steel plates enclosing a unique burglary-resistant high security material and an ARMOR steel plate barrier protecting the entire door.



Armor Plate Door

The HS6743 and HS7943 Features:

U.L. Listed TL-15 burglary and fire resistant high security gun safe.

2¾" thick door constructed with 1" thick solid steel plate and an inner steel plate enclosing a unique burglary-resistant, high security material.



1" Steel Plate Door

3½" thick body constructed with 1" thick solid steel plate inner wall and an outer steel plate enclosing a unique burglary-resistant, high security material.



1" Solid Steel Inner Wall

All HS Series Safes Feature:

Mercury Class IV fire protection of 1850°F for 2 hours. Designed to maintain an interior temperature of less than 350°F.

U.L. listed Group 2M lock with spy-proof key-locking dial, drill shattering hard plate and two additional spring-loaded relocking devices.

Plush tan pin-dot fabric interior.

5-point handle in brass or chrome and bold zinc die-cast polished brass or chrome logos.

10 massive 1½" solid steel chrome plated locking bolts.



Group 2M Lock



5-Spoke Handle



1½" Locking Bolts

HS Series - High Security
The Ultimate in Security and Fire Protection




HS Series - High Security





RF6528

Exterior
72" x 35" x 29½"
Gun Capacity
12-18-30
Weight
3,455 lbs.




NEW! HS7943

Exterior
79" x 43" x 29½"
Gun Capacity
12-23-35
Weight
6,840 lbs.



NEW! HS6743

Exterior
67" x 43" x 29½"
Gun Capacity
12-23-35
Weight
4,824 lbs.



Hardware Options



Chrome



Brass

Color Options

High Gloss



Platinum Metallic



Burgundy Metallic



Onyx



Pearl



Hunter Green Metallic



Macadamia Metallic



Charcoal Metallic

Textured



Sandstone



Granite



Black



Chocolate Brown



RF6528

HS7943 & HS6943



The BF Series Features:



1/2" Steel Plate Door

1/2" steel plate door combined with 1" **DryLight** insulation. (BF7250 is 3/8" steel plate.)



2" Wall Thickness

2" total wall thickness on all sides featuring our poured **DryLight** insulation and two layers of steel for exceptional fire and security protection.

U.L. Residential Security Container (RSC) Burglary Classification.



1 1/2" Locking Bolts

10 massive 1 1/2" chrome-plated bolts. Bolt detent system holds bolts in open position.

Mercury Class III fire protection of 1275°F for 90 minutes. Designed to maintain an interior temperature of less than 350°F.



Adjustable Hinges

Commercial grade, adjustable ball bearing hinges.

Dual fire seals with silicone seal on door jamb and Palusol seal on door.



Group II Lock

U.L. Listed Group II Lock with massive hard plate and two relocking devices.

Spy-proof, key-locking dial with decorative five-spoke handle.



5-Spoke Handle Standard

Unique mirrored back wall for added interior visibility.

Bold zinc die-cast polished brass or chrome logos.

4 pre-cut anchor holes and 1 pre-cut electrical access hole.



E-Z Slant-Out Interior

E-Z Slant-Out Interior for easy access to your long guns. Interior features rich pin-dot fabric and adjustable interior shelving.


BF[®] Series - Burglary / Fire
The Most Unique Gun Safe In the Industry




BF[®] Series - Burglary / Fire




NEW! **BF7250**
Exterior
 71¼" x 50" x 28"
Gun Capacity
 12-23-24-35-47
Weight
 1,736 lbs.




BF7240
Exterior
 71¼" x 40" x 26"
Gun Capacity
 12-18-24-30-42 / Optional 58 Gun
Weight
 1,305 lbs.



BF6636
Exterior
 65¼" x 36" x 26"
Gun Capacity
 12-23-35
Weight
 1,249 lbs.



BF6030
Exterior
 59¼" x 30" x 26"
Gun Capacity
 12-18-30
Weight
 885 lbs.




BF6032
Exterior
 59¼" x 30" x 21"
Gun Capacity
 8-14-22
Weight
 810 lbs.



All BF[®] Series Safes Feature DryLight Insulation

American Security Product's **DryLight** (trademark pending) is an advanced poured concrete insulation material that eliminates the use of gypsum board and provides a dry and seamless barrier to protect valuables against intense fires and burglary attacks.



Hardware Options



Chrome



Brass

Color Options

High Gloss



Platinum Metallic



Burgundy Metallic



Onyx



Pearl



Hunter Green Metallic



Macadamia Metallic



Charcoal Metallic

Textured



Sandstone



Granite



Black




Chocolate Brown



Two-Tone Black/Onyx



Two-Tone Granite/Charcoal



BF7250 is 3/8" Plate



All SF Series Safes Feature:

¼" Steel Plate door with 3 layers of fire insulating material.

Mercury Class II fire protection of 1200°F for 60 minutes. Designed to maintain an interior temperature of less than 350°F.

Palusol™ door seal - expands up to 8 times its original thickness when exposed to high temperatures.

Body constructed of 12-gauge solid steel plate with a fire insulating material.

Group II, key-changeable lock with internal relocker, spy-proof key-locking dial and drill-resistant hardplate.

Optional electronic lock available.

3-point handle in brass or chrome and bold zinc die-cast polished brass or chrome logos.

3-way boltwork with 5 active 1¼" chrome-plated bolts and 3 deadbolts.

Adjustable ball bearing hinges.

All-velour interior including back-cover and firewalls.

Four (4) pre-cut anchor holes with mounting hardware included and one (1) pre-cut electrical access hole.

Available in several gloss and textured finishes.



¼" Steel Plate Door




Group II Lock



3-Spoke Handle



1¼" Locking Bolts



Adjustable Hinges



All Velour Interior

SF Series - Sixty Minute Fire

Quality Packed, Affordably Priced




NEW!

SF Series - Sixty Minute Fire




SF6036

Exterior
59" x 36" x 26"
Gun Capacity
17-17-34
Weight
718 lbs.




SF6030

Exterior
59¼" x 30" x 26"
Gun Capacity
14-14-28
Weight
646 lbs.




SF6032

Exterior
59¼" x 30" x 21"
Gun Capacity
10-10-20
Weight
576 lbs.



SF5924

Exterior
59¼" x 24" x 18"
Gun Capacity
8-8-16
Weight
462 lbs.



Hardware Options



Chrome



Brass

Color Options

High Gloss



Platinum Metallic



Burgundy Metallic



Onyx



Pearl



Hunter Green Metallic



Macadamia Metallic



Charcoal Metallic

Textured



Sandstone



Granite



Black



Chocolate Brown



Two-Tone Black/Onyx



Two-Tone Granite/Charcoal



LOCKING BOLTS

8 1/4"

WALLS

12 ga.

1/4" PLATE DOOR

4 1/4"



TF6036, TF6030, TF6032 and TF5924 Feature:



3/16" Steel Plate Door

3/16" Steel Plate door with 2 layers of fire insulating material.



Group II Lock

Mercury Class I fire protection of 1200°F for 30 minutes. Designed to maintain an interior temperature of less than 350°F.



3-Spoke Brass Handle

Palusol™ door seal - expands up to 8 times its original thickness when exposed to high temperatures.

Body constructed of 12-gauge (5924 - 14ga) solid steel plate with a fire insulating material.

Group II, key-changeable lock with spy-proof dial, internal relocker and drill resistant hardplate.



1 1/4" Locking Bolts

Optional electronic lock available.

3-point brass tri-spoke handle and bold zinc die-cast polished brass logo.



Adjustable Hinges

3-way boltwork with 5 active 1 1/4" chrome-plated bolts and 3 deadbolts.

Adjustable ball bearing hinges.



Mocha Fabric Interior

Textured Black exterior and Mocha fabric interior including back-cover and firewalls.

Four (4) pre-cut anchor holes with mounting hardware included and one (1) pre-cut electrical access hole.

TF Series - Thirty Minute Fire
An Unbeatable Value




(TF5517 - 1 Year Parts & Labor)



TF Series - Thirty Minute Fire

TF6036

Exterior
59" x 36" x 26"
Gun Capacity
17-17-34
Weight
602 lbs.




TF6030

Exterior
59¼" x 30" x 26"
Gun Capacity
14-14-28
Weight
528 lbs.




TF6032

Exterior
59¼" x 30" x 21"
Gun Capacity
10-10-20
Weight
472 lbs.



TF5924

Exterior
59¼" x 24" x 18"
Gun Capacity
8-8-16
Weight
388 lbs.



TF5517

Exterior
55¼" x 17¾" x 16"
Gun Capacity
11-Gun
Weight
286 lbs.



The TF5517 Features:

3/16" Steel Plate door with 2 layers of fire insulating material.

Mercury Class I fire protection of 1200°F for 30 minutes. Designed to maintain an interior temperature of less than 350°F.

Palusol™ door seal - expands up to 8 times its original thickness when exposed to high temperatures.

Body constructed of 14-gauge solid steel plate with a fire insulating material.

3-wheel combination lock with spy-proof dial and drill resistant hardplate.

Brass "L" handle and bold zinc die-cast polished brass logo.

3-way boltwork with 5 active 1" chrome-plated bolts and 3 deadbolts.

Textured Black exterior and Mocha fabric interior including back-cover and firewalls.

Durable hinges.

Four (4) pre-cut anchor holes with mounting hardware included and one (1) pre-cut electrical access hole.

Warranty: 1 Year Parts and Labor



TF6036



TF5517

TF6036, TF 6030
TF6032, TF5924

LOCKING BOLTS

8 1¼"

WALLS

12 ga.

3/16" PLATE DOOR

3⁵/₈"



(TF5924 - 14ga)

TF5517

LOCKING BOLTS

8 1"

WALLS

14 ga.

3/16" PLATE DOOR

3¼"




Horizontal Cabinet 1854-HCC

Shown Here With
Oak Cabinet
and Tan Cushion



Shown Above With
Cherry Cabinet and Black Cushion



8 Gun Interior



PROUDLY MADE IN THE U.S.A.

1854-HCC Features:

Attractive wood cabinet in oak or cherry finish with tan or black cushion conceals the horizontal safe discreetly and can be used as a comfortable bench seat in a bedroom, office or den.

Assisted by two hydraulic gas pistons, the door opens and closes gently.

Inside lined with rich pin dot fabric.

Mercury Class I fire at 1200°F for a period of 30 minutes. Designed to maintain an interior temperature of less than 350°F.

High-strength, double-wall unitized 12 ga. body and a 3/4" thick formed door.

Group II lock and front read dial protected by a drill-resistant hard plate.

5 one-inch, chrome-plated steel locking bolts.

Outside dimensions include wood cabinet: 22 1/2"H x 56 3/4"W x 24 1/4"D

Weight: 450 lbs.

Warranty: 1 Year Parts and Labor

AM Series

Model	Exterior	Door	Body	Bolts	Shelves	Weight
AM2020	20h x 20w x 20d	1 1/8"	12 ga.	6	1	158 lbs.
AM3020	20h x 20w x 20d	1 1/8"	12 ga.	8	2	215 lbs.
AM4020	20h x 20w x 20d	1 1/8"	12 ga.	8	3	270 lbs.



AM Series Features:

All-velour interior including back-cover and firewalls.

Deep blue textured finish with bold, elegant American Security logo.

Spy-proof dial and chrome "L" handle.

Adjustable ball bearing hinges.

High-strength unitized 12 ga. solid steel body.

Massive 1 1/8" recessed door constructed of a 1/4" solid steel plate and a fire insulating material.

3-wheel combination lock protected by a drill-resistant hard plate. (U.L. Listed Group II Combination or Electronic lock available).

3-way boltwork with 5 active 1 1/4" diameter chrome-plated steel locking bolts (2020 Model has 4 active locking bolts).

4 pre-cut anchor holes with mounting hardware included.

Fire protection of 1200°F for a period of 30 minutes. Designed to maintain an interior temperature of less than 350°F.

Warranty: 1 Year Parts and Labor

Home Safes

When a Smaller Safe is All You Need



Optional Quick Release Anchor Plate Assembly

PB2 w/5BE Lock

Deep blue textured finish with chrome hardware.

Heavy-duty chrome handle.

Strong, pry-resistant chrome locking bolt.

Interior cushioned with foam lining to protect against scratches.

Easy to change combination with programmable override code.

9 VDC battery provides over 5,000 openings with low-battery indicator.

External auxiliary battery connection.

Tamper-proof penalty lockout protects against manipulation attempts.

Optional: Quick Release Anchor Plate Assembly allows easy transfers with lock tabs and thumb screws, no tools necessary to transfer case. Pre-punched holes enable the case to be installed directly to most surfaces.

Exterior Dimension	Weight
8h x 12w x 4d	8



ES412 w/DL4000 Electronic Lock

One (1) auxiliary key-lock, low-battery indicator, bright blue LCD display, and power override battery box.

Heavy 16 ga. solid steel construction.

Strong, pry-resistant recessed 10 ga. door with internal hinges.

Two tempered-steel live bolts.

Fits in a drawer and only requires 5" clearance.

Excellent for protecting valuables, handguns or laptop computers.

Exterior Dimension	Weight
8h x 12w x 4d	19



Smith & Wesson® VersaVault - SWVV1014

Electronic lock with four button lighted keypad offers more than 65,000 possible combinations.

Key override system.

Designed to be secured for either vertical or horizontal installation with the steel mount plate.

Additional mount plates are available to secure valuables in transit.

A unique removable internal holster presents firearm for rapid response.

Internal illumination, tamper alarm and low-battery indicator are standard.

Exterior Dimension	Weight
8h x 12w x 4d	19

Handgun Safes

Fire Safes



Safe features:

U.L. Listed, 350°F, 1-Hr fire protection.

Units with DL4000 Electronic lock (ES) feature:

- Emergency key lock
- Low battery indicator
- Power override battery box
- Spy-proof feature to hide combo
- Motion detector with alarm

Models ES914 and ES149 come with drawer shelf, anchor holes and anchor hardware.

Mechanical combination units (FS) come with standard mechanical combination lock plus key lock.

Safe Specifications

Model	Inside Dimensions (HxWxD)	Outside Dimensions (HxWxD)	Weight
ES914	8 ⁹ / ₁₆ x 14 ¹ / ₄ x 9 ³ / ₄	14 x 19 ¹ / ₂ x 15 ³ / ₈	124
ES149	14 ³ / ₈ x 8 ³ / ₄ x 10	19 ¹ / ₂ x 14 x 15 ⁵ / ₁₆	126
FS914	8 ⁹ / ₁₆ x 14 ¹ / ₄ x 9 ³ / ₄	14 x 19 ¹ / ₂ x 15 ³ / ₈	124
FS149	14 ³ / ₈ x 8 ³ / ₄ x 10	19 ¹ / ₂ x 14 x 15 ⁵ / ₁₆	126

Electronic Safes



Safe features:

Small burglary resistant safes with state-of-the-art DL4000 digital electronic locking system.

The DL4000 Electronic Lock features:

- Emergency key lock
- Low battery indicator
- Power override battery box
- Spy-proof feature to hide combo
- Motion detector with alarm

Can be bolted to the wall, floor or put inside a safe.

Dual live bolts made of heavy-gauge steel.

Carpeted base.

Safe Specifications

Model	Inside Dimensions (HxWxD)	Outside Dimensions (HxWxD)	Weight
ES813	7 ¹³ / ₁₆ x 12 ¹ / ₁₆ x 5	8 x 12 ¹ / ₄ x 7 ³ / ₄	16
ES916	8 x 15 ³ / ₄ x 10 ⁵ / ₈	9 x 16 x 13 ¹ / ₈	30
ES1014	9 ¹ / ₂ x 13 ¹ / ₂ x 7	9 ³ / ₄ x 13 ³ / ₄ x 9 ³ / ₄	27
ES2014	19 ¹ / ₂ x 13 ¹ / ₂ x 9 ¹ / ₂	19 ³ / ₄ x 13 ³ / ₄ x 12 ¹ / ₄	47

Fire and Electronic Safes

As time goes on, all collections grow – not just guns, but personal heirlooms, business and family records, jewelry, photographs and works of art. Instead of buying three different safes over a lifetime, the AMSEC vault door turns your room into a security center. It is designed for easy installation that retrofits a standard 80" x 30" opening.

Massive 1" door is constructed of 1/8" inner and outer steel plates filled with a fire insulating material that provides a barrier against extreme heat. Select from four textured finishes.

Each vault door offers elegant scrollwork and pinstripes accompanied by the renowned American Security logo.

Group II, key-changeable lock with internal relocker, brass spy-proof key-locking dial and drill-resistant hardplate.

Decorative 3-point handle is standard.

5 massive 1¼" thick active bolts, with 5 deadbolts you can rest assured that your valuables are protected. (Note: no deadbolts required on in-swing door.)

Safety Lock Release: In case the door closes behind you, this safety feature allows you to exit the vault quickly.

Make your vault room double as a storm shelter with our in-swing vault door. Offering the same features as our standard vault door, the in-swing vault door will insure opening from the inside even if debris has blocked the door.

Minimum opening required:
79½" H x 29½" W

Door opening:
77½" H x 26½" W

In-Swing Door opening:
77½" H x 20-5/16" W

Weight:
395 lbs.

Hardware Options



Chrome



Brass

Color Options



Sandstone



Granite



Black



Chocolate Brown



Vault Door

Turns Any Room into a Security Center

Storage Cabinets



Elegant, well-appointed 2-drawer and 4-drawer interior chests are the most sophisticated way to store and display your jewelry collection and letter files. These stunning chests are finely crafted in solid-wood maple drawer fronts and maple veneer and finished in a rich honey maple stain.

Drawer Features:

2-DRAWER OPTION:

Has a top drawer and a non-lined bottom drawer that converts into a letter-size file drawer with a metal file bracket.

4-DRAWER OPTION:

Has two top drawers, a middle drawer, and a felt-lined bottom drawer. Both drawer options offer heavy-duty, ball-bearing drawer glides.

Storage Cabinet Specifications

Model	Outside Dimensions (HxWxD)	Weight
2-Drawer	16 ¾ x 16 x 15 ¾	32
4-Drawer	16 ¾ x 16 x 15 ¾	37

Stor-it Options

Stor-it-Pack



Door-mounted storage system designed to manage all your gear with multiple pouches, elastic shot shell holder and a clear license holder.

16" H x 18" W x 3" D

Stor-it-Shelves (BF Gun Safes Only)



Built with 16 ga. steel.

Two hand gun storage slots.

Raised edge on all shelves keeps items in place.

Convenient storage space.

27½" H x 14" W x 2" D

Storage Options

Electronic Lock Options

For quick and easy entry, an electronic lock is the choice to make. Locks are powered by batteries located in the dial and you can change your combination anytime.

AMSEC®



AMSEC's ESLXL Models

Available in Brass, Chrome and Black finish



Sargent & Greenleaf Model 6120

Round Keypad, Brass or Chrome finish



Sargent & Greenleaf Model 6120EZ

"EZ" Keypad, Brass or Chrome finish

LAGARD

LG Basic

Brass or Chrome finish



Other Options



Pistol Rack

This four-gun rack is ideal for organizing pistols inside your safe.



GunSaver Dehumidifier

Will constantly guard your guns against the threat of rust, pitting and moisture damage. Electrical access required.



Jewelry Tray

Tray conveniently fits into every safe. Burgundy felt lined. Dimensions: 10 3/8" x 9 3/8" x 2"



Desiccant

Prevents rust and moisture damage. Recommended for safes without electrical access.



Fluorescent Light Kits

One 22" fluorescent light mounted vertically in back of safe for all lower compartments and one 12" front top light for upper area. Includes connector cables, door switch and power strip.



"Premium" Upgrade Package for BF® and HS Safes

When you choose to upgrade your American Security BF® or HS Series with a "Premium" Package, we'll add on some of our most popular options including:



Pistol Rack



Dehumidifier



Jewelry Tray



Fluorescent Light Kit



Internal Power Outlet


Electronic Locks and Other Options

Features at a Glance


Model	Exterior Dimensions H x W x D	Gun Capacity	Weight	Bolts	Bolt Diameter	Warranty
HS SERIES						
RF6528	72" x 35" x 29½"	12-18-30	3,455	10	1½"	Lifetime
HS7943	79" x 43" x 29½"	12-23-35	6,840	10	1½"	Lifetime
HS6743	67" x 43" x 29½"	12-23-35	4,824	10	1½"	Lifetime
BF SERIES						
BF7250	71¼" x 50" x 28"	12-23-24-35-47	1,736	10	1½"	Lifetime
BF7240	71¼" x 40" x 26"	12-18-24-30-42	1,305	10	1½"	Lifetime
BF6636	65¼" x 36" x 26"	12-23-35	1,249	10	1½"	Lifetime
BF6030	59¼" x 30" x 26"	12-18-30	885	10	1½"	Lifetime
BF6032	59¼" x 30" x 21"	8-14-22	810	10	1½"	Lifetime
SF SERIES						
SF6036	59¼" x 36" x 26"	17-17-34	718	8	1¼"	Lifetime
SF6030	59¼" x 30" x 26"	14-14-28	646	8	1¼"	Lifetime
SF6032	59¼" x 30" x 21"	10-10-20	576	8	1¼"	Lifetime
SF5924	59¼" x 24" x 18"	8-8-16	462	8	1¼"	Lifetime
TF SERIES						
TF6036	59¼" x 36" x 26"	17-17-34	602	8	1¼"	Lifetime
TF6030	59¼" x 30" x 26"	14-14-28	528	8	1¼"	Lifetime
TF6032	59¼" x 30" x 21"	10-10-20	472	8	1¼"	Lifetime
TF5924	59¼" x 24" x 18"	8-8-16	388	8	1¼"	Lifetime
TF5517	55¼" x 17¾" x 16"	11	286	8	1"	1 Year Parts & Labor
HORIZONTAL CABINET						
HC1854	18" x 54¼" x 22"	8	450	5	1"	1 Year Parts & Labor

NOTE: Dimensions listed are exterior dimensions. Add 2" to overall depth for lock and handle on all safes.


RF6528 Body / Door



HS Series Body / Door




BF Series Body / Door




Features at a Glance

	U.L. Listing	Thickness		Fire Rating	Dial	Handle	Standard Interior
		Door <i>Overall/Steel Plate</i>	Body				
	TL30	5¾"	3½"	2 Hr / 1850° F	Spy-Proof, Key-Lock	5-spoke	Tan Pin-Dot
	TL15	5¾" / 1"	3½"	2 Hr / 1850° F	Spy-Proof, Key-Lock	5-spoke	Tan Pin-Dot
	TL15	5¾" / 1"	3½"	2 Hr / 1850° F	Spy-Proof, Key-Lock	5-spoke	Tan Pin-Dot
	RSC	4¾" / ½"	2"	90 min / 1275° F	Spy-Proof, Key-Lock	5-spoke	Tan Pin-Dot
	RSC	4¾" / ½"	2"	90 min / 1275° F	Spy-Proof, Key-Lock	5-spoke	Tan Pin-Dot
	RSC	4¾" / ½"	2"	90 min / 1275° F	Spy-Proof, Key-Lock	5-spoke	Tan Pin-Dot
	RSC	4¾" / ½"	2"	90 min / 1275° F	Spy-Proof, Key-Lock	5-spoke	Tan Pin-Dot
	RSC	4¾" / ½"	2"	90 min / 1275° F	Spy-Proof, Key-Lock	5-spoke	Tan Pin-Dot
	B-Rate	4¼" / ¼"	12 ga.	60 min / 1200° F	Spy-Proof, Key-Lock	3-spoke	Tan Velour
	B-Rate	4¼" / ¼"	12 ga.	60 min / 1200° F	Spy-Proof, Key-Lock	3-spoke	Tan Velour
	B-Rate	4¼" / ¼"	12 ga.	60 min / 1200° F	Spy-Proof, Key-Lock	3-spoke	Tan Velour
	B-Rate	4¼" / ¼"	12 ga.	60 min / 1200° F	Spy-Proof, Key-Lock	3-spoke	Tan Velour
	B-Rate	3⅝" / ⅜"	12 ga.	30 min / 1200° F	Spy-Proof	3-spoke	Mocha Fabric
	B-Rate	3⅝" / ⅜"	12 ga.	30 min / 1200° F	Spy-Proof	3-spoke	Mocha Fabric
	B-Rate	3⅝" / ⅜"	12 ga.	30 min / 1200° F	Spy-Proof	3-spoke	Mocha Fabric
	B-Rate	3⅝" / ⅜"	14 ga.	30 min / 1200° F	Spy-Proof	3-spoke	Mocha Fabric
	B-Rate	3¼" / ⅜"	14 ga.	30 min / 1200° F	Spy-Proof	3-spoke	Mocha Fabric
	B-Rate	¾"	12 ga.	45 min / 1200° F	Spy-Proof	"T" Handle	Tan Pin Dot

SF Series Body / Door



TF Series Body / Door





American Security Products

11925 Pacific Avenue, Fontana, CA 92337

951-685-9680

www.amsecusa.com

AMSEC reserves the right to update products as necessary. AMSEC is not responsible for typographical errors.

Part #4305172